



CABLE TECHNOLOGY, INC.

73 RIVER ROAD - WILLINGTON, CT 06279 - (860) 429 - 7889 FAX (860) 429 - 3615

9/C COMPOSITE CT-E939A

FIVE CONDUCTOR
COMPONENT
SHIELDED:

FIVE (5) #24 19/36 TC INSULATED WITH .010" PVC .044" DIA. EACH
CABLED TOGETHER WITH A 2"-3" LAY, FILLER
AND A #24 7/32 TC DRAIN WIRE
WRAP WITH ALUMINUM/MYLAR TAPE SHIELD WITH 25% MIN.
OVERLAP (FOIL FACING IN)

- 1) BLACK
- 2) BROWN
- 3) GREEN
- 4) RED
- 5) WHITE

FOUR SINGLES:

FOUR (4) #18 41/34 TC INSULATED WITH .010" PVC .066" DIA. EACH

- 1) BROWN
- 2) ORANGE
- 3) RED
- 4) GREEN W/ YELLOW STRIPE

CABLING:

CABLE THE FIVE CONDUCTOR COMPONENT AND THE FOUR
SINGLES TOGETHER WITH A 4"-5" LAY AND FILLER

TAPE SEPARATOR:

WRAP WITH A PAPER TAPE

JACKET:

.065" PRESSURE EXTRUDED OIL RESISTANT 105°C BLACK PVC

OD:

.380" MAX

PRINT IN WHITE:

E83208 RU STYLE 2661 105°C 300V VW-1...LL52835 CSA AWM I/II A/B
105°C 300V FT-4
PRINTED AT INTERVALS OF 24" OR LESS

(0741)

NOTE:

CABLE MUST CONFORM TO UL 758 & CSA C22.2 N0.210

I HAVE REVIEWED ABOVE SPECIFICATION AND IT CONFORMS TO ITEM ORDERED UNDER
PO#
NOTE AND EXCEPTIONS HERE →

SIGNED: _____ DATED: _____
CTE939A
