



Part Number: 1018A

Thermocouple Extension, (1 pr) 16 AWG Solid Type KX, PVC/PVC, Foil Shld, CMG

Product Description

One 16 AWG pair solid Type KX conductors, PVC insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

| AWG | Stranding | Material | No. of Pairs |
|------------------------------------|-----------|------------------|--------------|
| 16 | Solid | Chromel & Alumel | 1 |
| Total Number of Conductors: | | | 2 |

Insulation:

| Material | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.085 in | 0.017 in |

Color Chart 1:

| Number | Color |
|--------|--------------|
| 1 | Yellow & Red |

Outershield 1:

| Type | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|------------------------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Tape | Aluminum Foil-Polyester Tape | Beldfoil® | 100 % | TC - Tinned Copper | 18 | 7x26 mm |

Outerjacket 1:

| Material | Nominal Diameter | Ripcord |
|--------------------------|------------------|---------|
| PVC - Polyvinyl Chloride | 0.247 in | Yes |

| | |
|----------------------|--|
| Print Legend: | BELDEN-M 1018A E34972 1PR16 SHIELDED (UL) CMG 105C OR PLTC OR ITC SUN RES OR AWM 2464 80C 300V OR C(UL) CMG THCP L EXTN KX----FT4 IEEE1202 (2FT, 7 DIGIT SEQUENTIAL NUMBER) FEET |
|----------------------|--|

Electrical Characteristics

Conductor DCR:

| Element | Nominal Conductor DCR | Nominal Outer Shield DCR |
|------------|-----------------------|--------------------------|
| CHROMEL | 147 Ohm/1000ft | 38 Ohm/1000ft |
| CONSTANTAN | 58.9 Ohm/1000ft | |

Capacitance:

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Shield |
|---|--------------------------------------|
| 25 pF/ft | 51 pF/ft |

Inductance:

| Nominal Inductance |
|--------------------|
| 0.18 µH/ft |

Use

Safety

| | |
|--------------------------|--------------------|
| CSA Flammability: | FT4 |
| UL Flammability: | UL1685 FT4 Loading |

Temperature Range

| | |
|------------------------------|-----------------|
| Operating Temp Range: | -30°C To +105°C |
|------------------------------|-----------------|

Mechanical Characteristics

| | |
|------------------------------------|--------|
| Min Bend Radius/Minor Axis: | 2.5 in |
|------------------------------------|--------|

Part Number

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Standards

| | |
|-----------------------------------|----------------------------------|
| ANSI Compliance: | ANSI Specification |
| CA Prop 65 (CJ for Wire & Cable): | CA Prop 65 (CJ for Wire & Cable) |
| CEC/C(UL) Specification: | CEC/C(UL) Specification |
| MII Order #39 (China RoHS): | MII Order #39 (China RoHS) |
| NEC/(UL) Specification: | NEC/(UL) Specification |
| UL AWM Style: | AWM Specification |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | EU CE Mark |

History

| | |
|--------|---|
| Notes: | Chromel & Alumel - "Chromel and Alumel are Hoskins Manufacturing Company trademarks." |
|--------|---|

Product Variants

| Part Number | Color | Put-Up Type | Length |
|----------------|--------|-------------|----------|
| 1018A 00410000 | YELLOW | Reel | 10000 ft |
| 1018A 0041000 | YELLOW | Reel | 1000 ft |
| 1018A 0045000 | YELLOW | Reel | 5000 ft |

© 2016 Belden, Inc.

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.