



Part Number: 1114A

Thermocouple Extension, (1 pr) 16 AWG Solid Type EX, FEP/FEP, Foil Shld, PLTC, High-Temp

Product Description

One 16 AWG pair solid Type EX conductors, fluorinated ethylene propylene (FEP) insulation, overall Beldfoil® shield (100% coverage), fluorinated ethylene propylene (FEP) jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material		No. of Pairs
16	Solid	Chromel & Constantan		1
Total Number of Conductors:		2	2	

Insulation:

Material	
FEP - Fluorinated Ethylene Propylene	

Color Chart 1:

Number	Color
1	Purple & Red

Outershield 1:

Туре	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
	Aluminum Foil-Polyester Tape- Aluminum Foil	Beldfoil®	100 %	TC - Tinned Copper	18	7x26 mm

Outerjacket 1:

Material	Nominal Diameter		
FEP - Fluorinated Ethylene Propylene	0.172 in		
Print Legend:	BELDEN 1114A E34972 1PR16 SHIELDED (UL) CL3P 200C PLTC SUN RES THCPL EXTN EX (2 FT., 7 DIGIT SEQUENTIAL NUMBER) FEET		

Electrical Characteristics

Conductor DCR:

Element	Nominal Conductor DCR	Nominal Outer Shield DCR
CHROMEL	165 Ohm/1000ft	5.5 Ohm/1000ft
CONSTANTAN	121 Ohm/1000ft	

Use

Max Recommended Pulling Tension:	83 lbs

Safety

UL Flammability:	ULg10 Steiner Tunnel

Temperature Range

Non-UL Temp Rating:	200°C
Operating Temp Range:	-70°C To +200°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	1.75 in

Part Number

Plenum (Y/N):	Yes

Standards

ANSI Compliance:	ANSI Specification
CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)

NEC/(UL) Specification:	NEC/(UL) Specification	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	EU CE Mark	

History

Notes:	Chromel & Constantan = "Constantan is a Hoskins Manufacturing Company trademark."

Product Variants

Part Number	Color	Put-Up Type	Length
1114A 0075000	VIOLET	Reel	5000 ft

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Part # PF_1114A | Page 3 of 3 | May 25, 2016

Belden Inc. | belden.catalog.belden.com/en/Products/Detail/PF_1114A