



Part Number: 129463

Blue Hose®, (1 pr) 20 AWG (7x28) TC, PE/PVC, Foil+TC
Braid Shld, Alum Armor, CM

Product Description

One 20 AWG pair stranded (7x28) tinned copper conductors, polyethylene insulation, overall Beldfoil® (100% coverage) plus tinned copper braid shield (55% coverage), PVC inner jacket, aluminum interlocked armor, PVC outer jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
20	7x28	TC - Tinned Copper	0.038 in	1
Total Number of Conductors:				2

Insulation:

Material	Nominal Diameter
PE - Polyethylene	0.076 in

Color Chart 1:

Number	Color
1	Clear & Blue

Stranding:

Lay Length	Diameter
Yes mm	0.154 mm

Outershield 1:

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	20	7x28H mm
Braid	2	TC - Tinned Copper		55 %			

Outerjacket 1:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.238 in
	0.541 in

Armor:

Type of Armor	Material	Diameter over Armoring
Interlocked Armor	Aluminum	0.441 mm

Electrical Characteristics**Conductor DCR:**

Nominal Conductor DCR	Nominal Outer Shield DCR
9.5 Ohm/1000ft	4.1 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
19.7 pF/ft	36 pF/ft

Other Electrical Characteristic 1:	DC Resistance Unbalance: .77 Ohms/1000 ft Max
---	---

Impedance:

Nominal Characteristic Impedance
78 Ohm

High Frequency (Nominal/Typical):

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.6 db/100ft
10 MHz	2.1 db/100ft
50 MHz	5 db/100ft
100 MHz	7.5 db/100ft
200 MHz	11 db/100ft
400 MHz	16 db/100ft

Delay:

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.54 ns/ft	66 %

High Freq:

Frequency [MHz]
1 MHz
10 MHz
50 MHz
100 MHz
200 MHz
400 MHz

Inductance:

Nominal Inductance
0.12 μ H/ft

Voltage:

UL Voltage Rating
300 V RMS

Use

Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	200 lbs

Safety

UL Flammability:	UL1685 UL Loading
------------------	-------------------

Temperature Range

Operating Temp Range:	-40°C To +60°C
-----------------------	----------------

Mechanical Characteristics

Min Bend Radius/Minor Axis:	6.5 in
-----------------------------	--------

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
-----------------------------------	----------------------------------

CEC/C(UL) Specification:	CEC/C(UL) Specification
Customer Part Number Reference Spec:	Allen Bradley P/N 1770-CD
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)

History

Product Variants

Part Number	Color	Put-Up Type	Length
129463 J221000	BLUE, STRONG	Reel	1000 ft
129463 J226000	BLUE, STRONG	Reel	6000 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.