



Part Number: 1359A

FOUNDATION Fieldbus, (50 pr) 18 AWG (7x26) TC, PO/PVC, Foil Shld, PLTC, CMG, CMX-Outdoor

Product Description

Fifty 18 AWG pairs stranded (7x26) tinned copper conductors, polyolefin insulation, individual and overall Beldfoil® shield (100% coverage), PVC jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

No. of Pairs	
50	
Total Number of Conductors:	100

Insulation:

Material
PO - Polyolefin

Color Chart 1:

Number	Color
1	Blue & Orange Numbered 1
2	Blue & Orange Numbered 2
3	Blue & Orange Numbered 3
4	Blue & Orange Numbered 4
5	Blue & Orange Numbered 5

6	Blue & Orange Numbered 6
7	Blue & Orange Numbered 7
8	Blue & Orange Numbered 8
9	Blue & Orange Numbered 9
10	Blue & Orange Numbered 10
11	Blue & Orange Numbered 11
12	Blue & Orange Numbered 12
13	Blue & Orange Numbered 13
14	Blue & Orange Numbered 14
15	Blue & Orange Numbered 15
16	Blue & Orange Numbered 16
17	Blue & Orange Numbered 17
18	Blue & Orange Numbered 18
19	Blue & Orange Numbered 19
20	Blue & Orange Numbered 20
21	Blue & Orange Numbered 21
22	Blue & Orange Numbered 22
23	Blue & Orange Numbered 23
24	Blue & Orange Numbered 24
25	Blue & Orange Numbered 25
26	Blue & Orange Numbered 26
27	Blue & Orange Numbered 27
28	Blue & Orange Numbered 28
29	Blue & Orange Numbered 29
30	Blue & Orange Numbered 30
31	Blue & Orange Numbered 31
32	Blue & Orange Numbered 32
33	Blue & Orange Numbered 33
34	Blue & Orange Numbered 34
35	Blue & Orange Numbered 35
36	Blue & Orange Numbered 36
37	Blue & Orange Numbered 37
38	Blue & Orange Numbered 38
39	Blue & Orange Numbered 39
40	Blue & Orange Numbered 40
41	Blue & Orange Numbered 41
42	Blue & Orange Numbered 42
43	Blue & Orange Numbered 43
44	Blue & Orange Numbered 44
45	Blue & Orange Numbered 45
46	Blue & Orange Numbered 46

47	Blue & Orange Numbered 47
48	Blue & Orange Numbered 48
49	Blue & Orange Numbered 49
50	Blue & Orange Numbered 50

Stranding:

Lay Length	Twists
2.25 in	5.3 twist/ft

Innershield:

Type	Material	Material Trade Name	Coverage [%]	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	20	7x28 mm
	TC - Tinned Copper				

Outershield 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	18	7x26 mm

Outerjacket 1:

Material	Nominal Diameter	Ripcord
PVC - Polyvinyl Chloride	1.55 in	Yes

Electrical Characteristics

Conductor DCR:

Individual Pair Nominal Shield DCR	Nominal Conductor DCR	Nominal Outer Shield DCR
7.5 Ohm/1000ft	5.86 Ohm/1000ft	4.9 Ohm/1000ft

Capacitance:

Max. Capacitance Unbalance	Nom. Capacitance Conductor to Shield	Nom. Mutual Capacitance
1.2 pF/ft	45 pF/ft	24 pF/ft

Other Electrical Characteristic 1:	Max Propagation Delay Change From 7.812 kHz to 39.06 kHz: 518 pS/ft
---	---

Other Electrical Characteristic 2:	31.25 KBits/sec
---	-----------------

High Frequency (Nominal/Typical):

Nom. Insertion Loss
0.08 db/100ft

Delay:

Nominal Velocity of Propagation (VP) [%]
66 %

High Freq:

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Max./Min. Input Impedance (unFitted)
	0.091 db/100ft	100 Ohm
0.03125 MHz		
0.039 MHz		
0.039 MHz		

Current:

Element	Max. Recommended Current [A]
Per Conductor	5.2 Amps

Inductance:

Nominal Inductance
0.19 μ H/ft

Voltage:

UL Voltage Rating
300 V RMS

Use

Suitability - Oil Resistance:	Yes
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	2892 lbs

Safety

ISO/IEC Flammability:	60332-3-24 (Category C)
UL Flammability:	UL1685 Vertical Tray Flame Test

Temperature Range

Operating Temp Range:	-40°C To +105°C
UL Temp Rating:	105°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	15.5 in
-----------------------------	---------

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CEC/C(UL) Specification:	CEC/C(UL) Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

History

Product Variants

Part Number	Color	Put-Up Type	Length
1359A 0031000	ORANGE	Reel	1000 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.