



**Part Number:** 1361A

FOUNDATION Fieldbus, (2 pr) 16 AWG (7x24) TC, PO/PVC, Foil Shld, CMG, PLTC-ER

## Product Description

Two 16 AWG pairs stranded (7x26) tinned copper conductors, polyolefin insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

## Product Specifications

## Technical Specifications

### Construction and Dimensions

#### Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
16	7x24	TC - Tinned Copper	0.059 in	2
<b>Total Number of Conductors:</b>				4

#### Insulation:

Material
PO - Polyolefin

#### Color Chart 1:

Number	Color
1	Blue & Orange Numbered 1
2	Blue & Orange Numbered 2

#### Stranding:

Lay Length	Twists
2.5 in	5 twist/ft

**Innershield:**

Type	Material	Material Trade Name	Coverage [%]	Drainwire AWG
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	20

**Outershield 1:**

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	16	7x24 mm

**Outerjacket 1:**

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.58 in

**Electrical Characteristics**

**Conductor DCR:**

Individual Pair Nominal Shield DCR	Nominal Conductor DCR	Nominal Outer Shield DCR
7.5 Ohm/1000ft	4.2 Ohm/1000ft	4.9 Ohm/1000ft

**Capacitance:**

Max. Capacitance Unbalance	Nom. Capacitance Conductor to Shield	Nom. Mutual Capacitance
1.2 pF/ft	45 pF/ft	24 pF/ft

<b>Other Electrical Characteristic 1:</b>	Max Propagation Delay Change From 7.812 kHz to 39.06 kHz: 518 pS/ft
---	---

<b>Other Electrical Characteristic 2:</b>	31.25 KBits/sec
---	-----------------

**High Frequency (Nominal/Typical):**

Nom. Insertion Loss
0.08 db/100ft

**Delay:**

Nominal Velocity of Propagation (VP) [%]
66 %

**High Freq:**

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Max./Min. Input Impedance (unFitted)
	0.091 db/100ft	100 Ohm
0.03125 MHz		
0.039 MHz		
0.039 MHz		

#### Current:

Element	Max. Recommended Current [A]
Per Conductor	5.2 Amps

#### Inductance:

Nominal Inductance
0.19 $\mu$ H/ft

#### Voltage:

UL Voltage Rating
300 V RMS

#### Use

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	143 lbs

#### Safety

ISO/IEC Flammability:	60332-3-24 (Category C)
IEEE Flammability:	1202
UL Flammability:	UL1685 FT4 Loading

#### Temperature Range

Operating Temp Range:	-40°C To +105°C
UL Temp Rating:	105°C

#### Mechanical Characteristics

Min Bend Radius/Minor Axis:	5.8 in
-----------------------------	--------

#### Part Number

Plenum (Y/N):	No
---------------	----

## Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CEC/C(UL) Specification:	CEC/C(UL) Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

## History

## Product Variants

Part Number	Color	Put-Up Type	Length
1361A 0031000	ORANGE	Reel	1000 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.