



Part Number: 2109A

FOUNDATION Fieldbus, (1 pr) 16 AWG (7x24) TC, XLP/FR-PVC, Foil Shld, 300V, CMG, PLTC-ER

Product Description

One 16 AWG pair stranded (7x24) tinned copper conductors, cross-linked polyolefin, overall Beldfoil® shield (100% coverage), flame retardant PVC jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	No. of Pairs
16	7x24	TC - Tinned Copper	1
Total Number of Conductors:			2

Insulation:

Material
XLP - Cross-linked Polyolefin

Color Chart 1:

Number	Color
1	Blue & Orange Numbered 1

Stranding:

Lay Length
0.091 mm

Innershield:

Type	Material	Material Trade Name	Coverage [%]	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	18	7x26 mm
	TC - Tinned Copper				

Outerjacket 1:

Material	Nominal Diameter	Ripcord
FR PVC - Flame Retardant Polyvinyl Chloride	0.365 in	Yes

Electrical Characteristics**Conductor DCR:**

Nominal Conductor DCR
4.2 Ohm/1000ft

Capacitance:

Max. Capacitance Unbalance	Nom. Capacitance Conductor to Shield
1.2 pF/ft	22 pF/ft
Other Electrical Characteristic 1:	Max Propagation Delay Change From 7.812 kHz to 39.06 kHz: 518 pS/ft
Other Electrical Characteristic 2:	31.25 KBits/sec

High Frequency (Nominal/Typical):

Nom. Insertion Loss
0.065 db/100ft

Delay:

Nominal Velocity of Propagation (VP) [%]
64 %

High Freq:

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Max./Min. Input Impedance (unFitted)
	0.091 db/100ft	100 Ohm
0.03125 MHz		
0.039 MHz		
0.039 MHz		

Current:

Element	Max. Recommended Current [A]
Per Conductor	11.6 Amps

Inductance:

Nominal Inductance

0.22 μ H/ft

Voltage:

Description

UL Voltage Rating

Voltage Rating (V)

CSA CIC type TC

300 V RMS

300 V RMS

Use

Suitability - Oil Resistance:

Yes

Suitability - Indoor:

Yes

Suitability - Outdoor:

Yes

Suitability - Sunlight Resistance:

Yes

Max Recommended Pulling Tension:

93 lbs

Safety

CSA Flammability:

FT4

ISO/IEC Flammability:

60332-3-24 (Category C)

UL Flammability:

UL1685 FT4 Loading

Temperature Range

Installation Temp Rating:

-25°C

Operating Temp Range:

-25°C Cold Impact -40°C To +90°C -55°C Cold Bend

UL Temp Rating:

90°C Wet/Dry

Mechanical Characteristics

Min Bend Radius/Minor Axis:

3.75 in

Part Number

Plenum (Y/N):

No

Standards

CA Prop 65 (CJ for Wire & Cable):

CA Prop 65 (CJ for Wire & Cable)

CSA AWM Specification:

CSA Specification

MII Order #39 (China RoHS):

MII Order #39 (China RoHS)

NEC/(UL) Specification:

NEC/(UL) Specification

Other Specification:	Other Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

History

Product Variants

Part Number	Color	Put-Up Type	Length
2109A 0031000	ORANGE	Reel	1000 ft
2109A 0035000	ORANGE	Reel	5000 ft
2109A 0061000	BLUE, LIGHT	Reel	1000 ft
2109A 0065000	BLUE, LIGHT	Reel	5000 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.