



**Part Number:** 24500

600V ACIC, (36 pr) 16 AWG (7x24) TC, PVC/PVC/PVC, Foil Shld, Alum Armor

## Product Description

Thirty-six 16 AWG pairs stranded (7x24) tinned copper conductors, PVC insulation, PVC inner jacket, individual plus an overall Beldfoil® shield (100% coverage), aluminum interlocked armor, PVC outer jacket.

## Product Specifications

## Technical Specifications

### Construction and Dimensions

#### Conductor:

AWG	Stranding	Material	No. of Pairs
16	7X24	TC - Tinned Copper	1
<b>Total Number of Conductors:</b>			2

#### Insulation:

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.03 in

#### Color Chart 1:

Number	Color
1	Black & White

#### Innerjacket:

Material	Nominal Diameter	Ripcord
PVC - Polyvinyl Chloride	0.34 in	Yes

#### Outershield 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	18	7x26 mm

#### Outerjacket 1:

Material	Nominal Diameter	Ripcord	Separator Material
PVC - Polyvinyl Chloride	0.64 in	Yes	Polyester
	0.64 in		

#### Armor:

Type of Armor	Material
Interlocked Armor	Aluminum

## Electrical Characteristics

#### Conductor DCR:

Element	Individual Pair Nominal Shield DCR	Nominal Conductor DCR
16 AWG	6.7 Ohm/1000ft	4.2 Ohm/1000ft
22 AWG		14.7 Ohm/1000ft

#### Voltage:

Description	Voltage Rating [V]
CEC ACIC	600 V

## Use

Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	94 lbs

## Safety

CSA Flammability:	FT4
-------------------	-----

## Temperature Range

Dry Temp Range:	-40°C To +105 °C
Installation Temp Range:	-25°C To +105 °C
Wet Temp Range:	-40°C To +75°C

## Mechanical Characteristics

Min Bend Radius/Minor Axis:	7.7 in
-----------------------------	--------

## Part Number

Plenum (Y/N):	No
---------------	----

## Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CSA AWM Specification:	CSA Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
Other Specification:	Other Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)

## History

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.