



**Part Number:** 27090R

600V Tray, (12) 14 AWG (7x22) TC, XLP/CPE, TC

## Product Description

Twelve 14 AWG stranded (7x22) tinned copper conductors, cross-linked polyolefin insulation, chlorinated polyethylene jacket.

## Product Specifications

## Technical Specifications

### Construction and Dimensions

#### Conductor:

AWG	Stranding	Material	No. of Conductors
14	7x22	TC - Tinned Copper	12
<b>Total Number of Conductors:</b>			12

#### Insulation:

Material
XLPE - Cross Linked Polyethylene

#### Color Chart 1:

Number	Color
1	Black
2	Red
3	Blue
4	Orange
5	Yellow
6	Brown
7	Red/Black
8	Blue/Black
9	Orange/Black
10	Yellow/Black
11	Brown/Black
12	Black/Red

#### Outershield 1:

Material
Unshielded

#### Outerjacket 1:

Material	Nominal Diameter
CPE - Chlorinated Polyethylene	0.69 in

## Electrical Characteristics

#### Conductor DCR:

Nominal Conductor DCR
2.6 Ohm/1000ft

#### Current:

Max. Recommended Current [A]
7.5 A

#### Voltage:

UL Voltage Rating
600 V RMS

## Use

Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	655 lbs

## Safety

C(UL) Flammability:	FT4
ICEA Flammability:	T-29-520
IEEE Flammability:	1202
Other Flammability:	VW-1 rated Conductors
UL Flammability:	UL1685 UL Loading

## Temperature Range

Dry Temp Range:	-30°C To +90 °C
Wet Temp Range:	-30°C To +90°C

## Mechanical Characteristics

Min Bend Radius/Minor Axis:	6.9 in
-----------------------------	--------

## Part Number

Plenum (Y/N):	No
---------------	----

## Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification
Other Specification:	Other Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

## History

© 2016 Belden, Inc.

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an 'AS IS' basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.