



Part Number: 27847

600V Teck 90, (10) 14 AWG (7x22) BC+Grd, XLPE/PVC/PVC, Alum Armor, MC

Product Description

14 AWG stranded (7x22) bare copper conductors plus ground wire, cross-linked polyethylene insulation, PVC inner jacket, aluminum armor, PVC outer jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

Element	AWG	Stranding	Mate	rial	No. of Conductors
	14	7x22	BC - E	are Copper	10
Ground Wire	14	7x22	BC - E	are Copper	
Total Number of Conductors: 10					

Insulation:

Material	Nominal Wall Thickness
XLPE - Cross Linked Polyethylene	0.03 in

Color Chart 1:

Number	Color
1	Black
2	Red
3	Blue
4	Orange
5	Yellow
6	Brown
7	Red/Black
8	Blue/Black
9	Ornage/Black
10	Yellow/Black

Stranding:

Lay Length		
PVC mm		

Innerjacket:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.67 in

Outershield 1:

Material	
Unshielded	

Outerjacket 1:

Nominal Diameter	
1.04 in	

Armor:

Type of Armor	Material	Diameter over Armoring
Interlocked Armor	Aluminum	0.93 mm

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR	
2.6 Ohm/1000ft	

Current:

7.5 Amps per conductor @ 25°C

Voltage:

UL Voltage Rating	
600 V RMS	

Use

Suitability - Burial:	Yes
Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	321 lbs

Safety

CSA Flammability:	FT4
IEEE Flammability:	1202
Other Flammability:	ICEA T-29-520
UL Flammability:	UL1685 UL Loading

Temperature Range

Dry Temp Range:	-40°C To +90 °C
Operating Temp Range:	-40°C To +90°C
Wet Temp Range:	-40°C To +90°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	12.5 in

Part Number

Plenum (Y/N):	No

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)	
CSA AWM Specification:	CSA Specification	
Mll Order #39 (China RoHS):	MII Order #39 (China RoHS)	
NEC/(UL) Specification:	NEC/(UL) Specification	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will, Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Part # PF_27847 | Page 4 of 4 | May 25, 2016 Belden Inc. | belden.catalog.belden.com/en/Products/Detail/PF_27847