



Part Number: 28624AS

600V Tray, (19) 16 AWG (7x24) BC, PVC-NYL/PVC, Foil

Shld, TC-ER

# **Product Description**

Nineteen 16 AWG stranded (7x24) bare copper conductors, PVC/Nylon insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

# **Product Specifications**

# **Technical Specifications**

# **Construction and Dimensions**

#### Conductor:

Element	AWG	Stranding	Material	No. of Conductors
	16	7×24	BC - Bare Copper	19
No Ground				

Total Number of Conductors:	19

#### Insulation:

Material		
PVC/Nylon - Polyvinyl Chloride/Nylon		

#### Color Chart 1:

Number	Color
1	Black
2	Red
3	Blue
4	Orange
5	Yellow
6	Brown
7	Red/Black
8	Blue/Black
9	Orange/Black
10	Yellow/Black
11	Brown/Black
12	Black/Red
13	Blue/Red
14	Orange/Red
15	Yellow/Red
16	Brown/Red
17	Black/Blue
18	Red/Blue
19	Orange/Blue

### Stranding:

Lay Length		
N mm		

### Outershield 1:

Туре	e Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	MOO %	TC - Tinned Copper	16	7x24 mm

### Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.625 in	o.o6 in

# **Electrical Characteristics**

#### **Conductor DCR:**

Nominal Conduct	or DCR		
4.2 Ohm/1000ft			

#### **Current:**

#### Max. Recommended Current [A]

4 Amps per conductor @ 30°C

### Voltage:

#### Voltage Rating [V]

600 Volts RMS

# Use

Suitability - Burial:	Yes
Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	384 lbs

### Safety

C(UL) Flammability:	FT4	
IEEE Flammability:	1202	
UL Flammability:	UL1685 UL Loading	

# **Temperature Range**

Dry Temp Range:	-30°C To +90°C
Wet Temp Range:	-30°C To +75°C

### **Mechanical Characteristics**

Min Bend Radius/Minor Axis:	6.37 in
-----------------------------	---------

### **Part Number**

Plenum (Y/N):	No
---------------	----

# **Standards**

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification
Other Specification:	Other Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

# **History**

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.