



Part Number: 28868

600V Teck-Style®, (4) 10 AWG (7x18) BC+Grd, XLPE/PVC/PVC, Steel Armor, MC

Product Description

Four 10 AWG stranded (7x18) bare copper conductors plus ground wire, cross-linked polyethylene insulation, PVC inner jacket, steel armor, PVC outer jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

| Element | AWG | Stranding | Material | No. of Conductors |
|-------------|-----|-----------|------------------|-------------------|
| | 10 | 7×18 | BC - Bare Copper | 4 |
| Ground Wire | 10 | 7×18 | BC - Bare Copper | |

| Total Number of Conductors | |
|-----------------------------|---|
| Total Number of Conductors: | 4 |

Insulation:

| Material | Nominal Wall Thickness |
|----------------------------------|------------------------|
| XLPE - Cross Linked Polyethylene | 0.03 in |

Color Chart 1:

| Number | Color |
|--------|--------|
| 1 | Black |
| 2 | Red |
| 3 | Blue |
| 4 | Orange |

Stranding:

| lav | Lenath |
|-----|--------|
| Luy | Length |
| | |

PVC mm

Innerjacket:

| Material | Nominal Diameter |
|--------------------------|------------------|
| PVC - Polyvinyl Chloride | o.56 in |

Outershield 1:

Material

Unshielded

Outerjacket 1:

Nominal Diameter

0.84 in

Armor:

| Type of Armor | Material | Diameter over Armoring |
|-------------------|----------|------------------------|
| Interlocked Armor | Steel | 0.75 mm |

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR

1.02 Ohm/1000ft

Current:

Max. Recommended Current [A]

24 Amps per conductor @ 30°C

Voltage:

UL Voltage Rating

600 V RMS

Use

| Suitability - Burial: | Yes |
|------------------------------------|---------|
| Suitability - Sunlight Resistance: | Yes |
| Max Recommended Pulling Tension: | 330 lbs |

Safety

| CSA Flammability: | FT4 |
|--------------------|---------------------------------|
| ICEA Flammability: | T-29-520 |
| IEEE Flammability: | 1202 |
| UL Flammability: | VW-1 Singles, UL1685 UL Loading |

Temperature Range

| Dry Temp Range: | -40°C To +90 °C |
|-----------------------|-----------------|
| Operating Temp Range: | -40°C To +90°C |
| Wet Temp Range: | -40°C To +90°C |

Mechanical Characteristics

| lin Bend Radius/Minor Axis: | 10.3 in |
|-----------------------------|---------|
|-----------------------------|---------|

Part Number

| num (Y/N): | No |
|------------|----|
|------------|----|

Standards

| CA Prop 65 (CJ for Wire & Cable): | CA Prop 65 (CJ for Wire & Cable) |
|-----------------------------------|----------------------------------|
| CSA AWM Specification: | CSA Specification |
| MII Order #39 (China RoHS): | MII Order #39 (China RoHS) |
| NEC/(UL) Specification: | NEC/(UL) Specification |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |

History

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

 $Belden \ declares \ this \ product \ to \ be \ in \ compliance \ with \ EU \ LVD \ (Low \ Voltage \ Directive \ 73/23/EEC), as a mended \ by \ directive \ 93/68/EEC.$