



Part Number: 29018

600V ACIC, (4) 16 AWG (7x24) BC+Grd, XLPE/PVC/PVC, Alum Armor

Product Description

Four 16 AWG stranded (7x24) bare copper conductors plus bare copper ground wire, cross-linked polyethylene insulation, PVC inner jacket, aluminum interlocked armor, PVC outer jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

Element	AWG	Stranding	Material	No. of Conductors
	16	7x24	BC - Bare Copper	4
Ground Wire	16	7x24	BC - Bare Copper	
Total Number of Conductors:				4

Insulation:

Material
XLPE - Cross Linked Polyethylene

Color Chart 1:

Number	Color
1	White and Numbered 1
2	Black and Numbered 2
3	Black and Numbered 3
4	Black and Numbered 4

Stranding:

Lay Length

PVC mm

Outersield 1:

Material

Unshielded

Outerjacket 1:

Material

PVC - Polyvinyl Chloride

Nominal Diameter

0.39 in

0.7 in

Armor:

Type of Armor

Material

Diameter over Armoring

Interlocked Armor

Aluminum

0.59 mm

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR

4.2 Ohm/1000ft

Current:

Max. Recommended Current [A]

10 Amps per conductor @ 25°C

Voltage:

Non-UL Voltage Rating

600 V RMS

Use

Suitability - Burial:

Yes

Suitability - Sunlight Resistance:

Yes

Max Recommended Pulling Tension:

82 lbs

Safety

CSA Flammability:

FT4

Temperature Range

Dry Temp Range:	-40°C To +90 °C
Non-UL Temp Rating:	90°C Wet/Dry
Wet Temp Range:	-40°C To +90°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	8.3 in
-----------------------------	--------

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CSA AWM Specification:	CSA Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)

History

© 2016 Belden, Inc.

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.