



Part Number: 29025

600V ACIC, (60) 16 AWG (7x24) BC+Grd,
XLPE/PVC/PVC, Alum Armor

Product Description

Sixty 16 AWG stranded (7x24) bare copper conductors plus bare copper ground wire, cross-linked polyethylene insulation, PVC inner jacket, aluminum interlocked armor, PVC outer jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

Element	AWG	Stranding	Material	No. of Conductors
	16	7x24	BC - Bare Copper	60
Ground Wire	16	7x24	BC - Bare Copper	
Total Number of Conductors:				60

Insulation:

Material
XLPE - Cross Linked Polyethylene

Color Chart 1:

Number	Color
1	White and Numbered 1
2	Black and Numbered 2
3	Black and Numbered 3
4	Black and Numbered 4

5	Black and Numbered 5
6	Black and Numbered 6
7	Black and Numbered 7
8	Black and Numbered 8
9	Black and Numbered 9
10	Black and Numbered 10
11	Black and Numbered 11
12	Black and Numbered 12
13	Black and Numbered 13
14	Black and Numbered 14
15	Black and Numbered 15
16	Black and Numbered 16
17	Black and Numbered 17
18	Black and Numbered 18
19	Black and Numbered 19
20	Black and Numbered 20
21	Black and Numbered 21
22	Black and Numbered 22
23	Black and Numbered 23
24	Black and Numbered 24
25	Black and Numbered 25
26	Black and Numbered 26
27	Black and Numbered 27
28	Black and Numbered 28
29	Black and Numbered 29
30	Black and Numbered 30
31	Black and Numbered 31
32	Black and Numbered 32
33	Black and Numbered 33
34	Black and Numbered 34
35	Black and Numbered 35
36	Black and Numbered 36
37	Black and Numbered 37
38	Black and Numbered 38
39	Black and Numbered 39
40	Black and Numbered 40
41	Black and Numbered 41
42	Black and Numbered 42
43	Black and Numbered 43
44	Black and Numbered 44
45	Black and Numbered 45

46	Black and Numbered 46
47	Black and Numbered 47
48	Black and Numbered 48
49	Black and Numbered 49
50	Black and Numbered 50
51	Black and Numbered 51
52	Black and Numbered 52
53	Black and Numbered 53
54	Black and Numbered 54
55	Black and Numbered 55
56	Black and Numbered 56
57	Black and Numbered 57
58	Black and Numbered 58
59	Black and Numbered 59
60	Black and Numbered 60

Stranding:

Lay Length
PVC mm

Outersheild 1:

Material
Unshielded

Outerjacket 1:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	1.27 in
	1.66 in

Armor:

Type of Armor	Material	Diameter over Armoring
Interlocked Armor	Aluminum	1.53 mm

Electrical Characteristics

Voltage:

Non-UL Voltage Rating
600 V RMS

Use

Suitability - Burial:	Yes
-----------------------	-----

Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	1015 lbs

Safety

CSA Flammability:	FT4
-------------------	-----

Temperature Range

Dry Temp Range:	-40°C To +90 °C
Non-UL Temp Rating:	90°C Wet/Dry
Wet Temp Range:	-40°C To +90°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	19.9 in
-----------------------------	---------

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CSA AWM Specification:	CSA Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)

History

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an 'AS IS' basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.