



Part Number: 29540

2000V UL Flex Motor VFD, (3) 6 AWG (7x19x27) TC+Grd, XLPE/PVC, Foil+TC Braid Shld, TC-ER

Product Description

Three 6 AWG stranded (7x19x27) tinned copper circuit conductors plus ground wire, cross-linked polyethylene insulation, overall Duofoil® tape (100% coverage) plus a tinned copper braid shield (85% coverage), PVC jacket.

Product Specifications

Technical Specifications

Suitable Applications:	AC Motor drives, VFD, Variable Frequency drives
-------------------------------	---

Construction and Dimensions

Conductor:

Element	AWG	Stranding	Material	No. of Conductors
	6	7x19x27	TC - Tinned Copper	3
Ground Wire	6	7x19x27	TC - Tinned Copper	

Total Number of Conductors:	3
------------------------------------	---

Insulation:

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.07 in
XLPE - Cross Linked Polyethylene	

Color Chart 1:

Number	Color
1	Black and Numbered 1
2	Black and Numbered 2
3	Black and Numbered 3
4	Green/Yellow

Stranding:

Lay Length
Y mm

Outershield 1:

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum Foil-Polyester Tape	Duofoil®	100 %	TC - Tinned Copper	12 (4x)	65x30 mm
Braid	2	TC - Tinned Copper		85 %			

Outerjacket 1:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	1.065 in

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR
0.41 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
40 pF/ft	72 pF/ft

Min Insulation Resistance:	300 Megaohms/1000 ft. MOhm*1000ft
-----------------------------------	-----------------------------------

Impedance:

Nominal Characteristic Impedance
60 Ohm

Current:

Max. Recommended Current [A]
75 Amps per conductor @ 30°C (per NEC)

Inductance:

Nominal Inductance

0.171 μ H/ft

Voltage:

Description	UL Voltage Rating	Voltage Rating [V]
CSA AWM I/II A/B	2000 V RMS (Flexible Motor Supply Cable)	1000 V RMS
	2000 V RMS (NEC Type TC)	

Use

Suitability - Oil Resistance:	Yes
Suitability - Burial:	Yes
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	1220 lbs

Safety

CSA Flammability:	FT4
IEEE Flammability:	1202
UL Flammability:	UL1685 UL Loading

Temperature Range

UL Temp Rating:	90°C Wet/Dry
-----------------	--------------

Mechanical Characteristics

Min Bend Radius/Minor Axis:	10.6 in
-----------------------------	---------

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CEC/C(UL) Specification:	CEC/C(UL) Specification
CSA AWM Specification:	CSA Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC Articles:	NEC Articles

NEC/(UL) Specification:	NEC/(UL) Specification
Other Specification:	Other Specification
PMSHA Specification:	PMSHA Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

History

Product Variants

Part Number	Color	Put-Up Type	Length
29540 0101000	BLACK	Reel	1000 ft
29540 0103500	BLACK	Reel	3500 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.