



Part Number: 29551C

1000V CSA VFD, (3) 12 AWG (7x20) BC+Grd, XLPE/PVC,

Foil Shld, FT4

# **Product Description**

Three 12 AWG stranded (7x20) bare copper circuit conductors plus three symmetrical ground wires, cross-linked polyethylene insulation, two spiral copper tape shields (100% Coverage), PVC jacket.

# **Product Specifications**

# **Technical Specifications**

Suitable Applications:  AC Motor drives, VFD, Variable Frequency drives
---

### **Construction and Dimensions**

#### Conductor:

Element	AWG	Stranding	Material	No. of Conductors
	12	7×20	BC - Bare Copper	3
Ground Wire	16 (x3)	7×24	BC - Bare Copper	

Total Number of Conductors: 3
-------------------------------

#### Insulation:

N	Material Mat	Nominal Wall Thickness
ΧI	LPE - Cross Linked Polyethylene	0.031 in

### Color Chart 1:

Number	Color
1	Black and Numbered 1
2	Black and Numbered 2
3	Black and Numbered 3

# Stranding:

Lay Length	
Y mm	

### Outershield 1:

Туре	Layer	Material	Coverage [%]
Tape	1	Spiral Copper	100 %
Tape	2	Spiral Copper	100 %

# Outerjacket 1:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.46 in

# **Electrical Characteristics**

### **Conductor DCR:**

Nominal Conductor DCR	
1.6 Ohm/1000ft	

#### **Current:**

Max. Recommend	ed Current [A]	
30 Amps per condu	ctor @ 25°C	

# Voltage:

Description	Voltage Rating [V]
CSA TYPE TC	1000 V RMS

# Use

Suitability - Oil Resistance:	Yes	
Suitability - Aerial:	No	
Suitability - Burial:	Yes	
Suitability - Indoor:	Yes	
Suitability - Outdoor:	Yes	
Suitability - Sunlight Resistance:	Yes	
Max Recommended Pulling Tension:	258 lbs	

### **Safety**

CSA Flammability:	FT4
IEEE Flammability:	1202

### **Temperature Range**

Non-UL Temp Rating:	go°C Wet/Dry
Operating Temp Range:	-40°C To +90°C Dry +90°C Wet

### **Mechanical Characteristics**

Min Bend Radius/Minor Axis:	4.6 in

#### **Part Number**

Plenum (Y/N):	No

#### **Standards**

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)	
CSA AWM Specification:	CSA Specification	
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	EU CE Mark	

#### **History**

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will, Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in comptiance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.