



Part Number: 3044A

300V, (2 pr) 16 AWG (7x24) BC, (1) 22 AWG (7x30) BC, FR-PVC/FR-PVC, Foil Shld, PLTC-ER, CMG

Product Description

Two 16 AWG pairs stranded (7x24) bare copper conductors, one 22 AWG stranded (7x30) bare copper conductor, twisted pairs, flame retardant PVC insulation, overall Beldfoil® shield (100% coverage), flame retardant PVC jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	No. of Conductors	No. of Triads
16	7x24	BC - Bare Copper	1	2
22	7x30	BC - Bare Copper		
Total Number of Conductors:			7	

Insulation:

Material
F-R PVC - Flame Retardant Polyvinyl Chloride

Color Chart 2:

Number	Number
1	Black & White & Red and Numbered 1
2	Black & White & Red and Numbered 2
3	Orange

Stranding:

Twists
6 twist/ft

Outershield 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	18	7x26 mm

Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
FR PVC - Flame Retardant Polyvinyl Chloride	0.483 in	0.053 in	Yes

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
3.7 Ohm/1000ft	4.9 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
54.1 pF/ft	97.3 pF/ft

Inductance:

Nominal Inductance
0.156 µH/ft

Voltage:

UL Voltage Rating
300 V RMS

Use

Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	259 lbs

Safety

CSA Flammability:	FT4
ICEA Flammability:	T-29-520
IEEE Flammability:	1202

UL Flammability:	UL1685 FT4 Loading
-------------------------	--------------------

Temperature Range

Operating Temp Range:	-30°C To +105°C
------------------------------	-----------------

Mechanical Characteristics

Min Bend Radius/Minor Axis:	4.75 in
------------------------------------	---------

Part Number

Plenum (Y/N):	No
----------------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CEC/C(UL) Specification:	CEC/C(UL) Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification
UL AWM Style:	AWM Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)

History

Notes:	Alternate color coding available upon request.
---------------	--

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.