



Part Number: 3077F

FOUNDATION Fieldbus, (1 pr) 22 AWG (7x30) TC, PO/PVC, Foil Shld, CMG, CMX-Outdoor, PLTC-ER

Product Description

One 22 AWG pair stranded (7x30) tinned copper conductors, polyolefin insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
22	7x30	TC - Tinned Copper	0.03 in	1
Total Number of Conductors:				2

Insulation:

Material
PO - Polyolefin

Color Chart 1:

Number	Color
1	Blue & Orange

Stranding:

Lay Length
1.5 in

Outershield 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	20	7x28 mm

Outerjacket 1:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.196 in
Print Legend:	BELDEN 3077F DATABUS(R) 31.25 KB/S E34972 2C22 SHIELDED (UL) 105C PLTC OR ITC SUN RES OR CM OR C(UL) CM (2 FT. 7 DIGIT SEQUENTIAL NUMBER) FEET

Electrical Characteristics**Conductor DCR:**

Individual Pair Nominal Shield DCR	Nominal Conductor DCR
11.4 Ohm/1000ft	17.1 Ohm/1000ft

Capacitance:

Max. Capacitance Unbalance	Nom. Capacitance Conductor to Shield	Nom. Mutual Capacitance
1.2 pF/ft	44 pF/ft	23.5 pF/ft
Other Electrical Characteristic 2:	31.25 KBits/sec	

High Frequency (Nominal/Typical):

Nom. Insertion Loss
0.14 db/100ft

Delay:

Nominal Velocity of Propagation (VP) [%]
66 %

High Freq:

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Max./Min. Input Impedance (unFitted)
	0.152 db/100ft	100 Ohm
0.03125 MHz		
0.039 MHz		
0.039 MHz		

Current:

Element	Max. Recommended Current [A]
Per Conductor	2.5 Amps

Inductance:

Nominal Inductance

0.2 μ H/ft

Voltage:

UL Voltage Rating

300 V RMS

Use

Max Recommended Pulling Tension:

27 lbs

Safety

UL Flammability:

UL1685 UL Loading

Temperature Range

Operating Temp Range:

-30°C To +105°C

UL Temp Rating:

105°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:

2.2 in

Part Number

Plenum (Y/N):

No

Standards

CA Prop 65 (CJ for Wire & Cable):

CA Prop 65 (CJ for Wire & Cable)

CEC/C(UL) Specification:

CEC/C(UL) Specification

MII Order #39 (China RoHS):

MII Order #39 (China RoHS)

NEC Articles:

NEC Articles

NEC/(UL) Specification:

NEC/(UL) Specification

EU Directive Compliance:

EU Directive 2003/11/EC (BFR)

EU CE Mark:

EU CE Mark

History

Notes:

Tape around pair has shorting fold. CPE & LSOH Jacket optional.

Product Variants

Part Number	Color	Put-Up Type	Length
3077F 0031000	ORANGE	Reel	1000 ft
3077F 003500	ORANGE	Reel	500 ft

© 2016 Belden, Inc.

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.