



Part Number: 3084A

DeviceNet™, (1 pr) 22 AWG (19x34) TC, (1 pr) 24 AWG (19x36) TC, PVC-FPE/PVC, Foil+TC Braid Shld, CL2, CMG

Product Description

One 22 AWG stranded (19x34) tinned copper conductors, one 24 AWG stranded (19x36) tinned copper conductors, PVC insulation (power), foam polyethylene (FPE) insulation (data), individual foil shield (100% coverage) plus an overall tinned copper braid (65% coverage), PVC jacket.

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	No. of Conductors	No. of Pairs
22	19x34	TC - Tinned Copper	4	1
24	19x36	TC - Tinned Copper		1

Insulation:

Element	Material
22	PVC - Polyvinyl Chloride
24	FPE - Foam Polyethylene

Color Chart 1:

Number	Color
22 AWG Pair	Red & Black
24 AWG Pair	Blue & White

Stranding:

Lay Length
1 MHz

Innershield:

Type	Layer	Material	Coverage [%]
Tape	22 AWG Pair	Aluminum Foil-Polyester Tape	100 %
Tape	24 AWG Pair	Aluminum Foil-Polyester Tape	100 %

Outershield 1:

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Braid	TC - Tinned Copper	65 %	TC - Tinned Copper	22	19x34 mm

Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.28 in	0.032 in

Electrical Characteristics

Conductor DCR:

Element	Max. Conductor DCR	Nominal Outer Shield DCR
22 AWG	17.5 Ohm/1000ft	3.2 Ohm/1000ft
24 AWG	28 Ohm/100m	

Capacitance:

Element	Nom. Capacitance Conductor to Conductor
24 AWG Pair	12 pF/ft

Impedance:

Nominal Characteristic Impedance	Nominal Characteristic Impedance Description
120 Ohm	24 AWG Pair

Delay:

Max. Delay	Max. Delay Description	Nominal Velocity of Propagation (VP) [%]	Nominal Velocity of Propagation (VP) Description
1.36 ns/ft	24 AWG Pair	75 %	24 AWG Pair

High Freq:

Element	Frequency [MHz]
24 AWG Pair Only	0.125 MHz
	0.5 MHz
	1 MHz

Current:

Max. Recommended Current [A]
1.7 Amps per conductor @ 25°C (24 AWG)
4 Amps per conductor @ 24 V per NEC CL2 (Power Pair)

Inductance:

Element	Nominal Inductance
22 AWG Pair	0.221 μ H/ft
24 AWG Pair	0.251 μ H/ft

Voltage:

UL Voltage Rating
300 V RMS (CL2, CMG)
300 V RMS (C(UL) AWM)
600 V RMS (UL AWM Style 20201)

Use

Suitability - Oil Resistance:	Yes
Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	65 lbs

Safety

CSA Flammability:	FT4
UL Flammability:	UL1685 FT4 Loading

Temperature Range

Operating Temp Range:	-20°C To +75°C
UL Temp Rating:	75°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	2.75 in
-----------------------------	---------

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
-----------------------------------	----------------------------------

CEC/C(UL) Specification:	CEC/C(UL) Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification
Other Specification:	Other Specification
UL AWM Style:	AWM Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

History

Notes:	Flex Life: +/- 90 Degree Flex Test, 2" Diameter, 2 lbs. tension: 2000 Cycles minimum. Meter marks on jacket to aid users in installation. ODVA DevaiceNet is an Open DeviceNet Vendor Association, Inc. trademark.
---------------	--

Product Variants

Part Number	Color	Put-Up Type	Length
3084A 0021000	RED	Reel	1000 ft
3084A T5U1000	GRAY T5U	Reel	1000 ft
3084A T5U2000	GRAY T5U	Reel	2000 ft
3084A T5U5000	GRAY T5U	Reel	5000 ft
3084A T5U500	GRAY T5U	Reel	500 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive g3/68/EEC.