



**Part Number:** 3119A

DeviceBus® for Phoenix Contact, (3 pr) 24 AWG (7x32),  
(3) 18 AWG (7x26) TC, PE/PVC/PUR, Foil Shld+Braid

## Product Description

Three 24 AWG pairs stranded (7x32) tinned copper conductors, three 18 AWG stranded (7x26) tinned copper conductors, PVC insulation (power), polyethylene insulation (data), overall Beldfoil® shield (100% coverage) plus a tinned copper braid (90% coverage), polyurethane jacket.

## Product Specifications

## Technical Specifications

### Construction and Dimensions

#### Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Conductors	No. of Pairs
24	7x32	TC - Tinned Copper	0.024 in		3
18	7x26	TC - Tinned Copper	0.06 in	3	

<b>Total Number of Conductors:</b>	9
------------------------------------	---

#### Insulation:

Element	Material
24	PE - Polyethylene
18	PVC - Polyvinyl Chloride

#### Color Chart 1:

Number	Color
1	White & Brown
24	Red
2	Pink & Gray
18	Blue
3	Yellow & Green
24	Green/Yellow Stripe
4	
18	
5	
24	
6	
18	

#### Outershield 1:

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire Diameter	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	0.024 mm	24	7x32 mm
Braid	2	TC - Tinned Copper		90 %				

#### Outerjacket 1:

Material	Nominal Diameter
PUR - Polyurethane	0.333 in

## Electrical Characteristics

#### Conductor DCR:

Element	Nominal Conductor DCR	Nominal Outer Shield DCR
24	23.4 Ohm/1000ft	2.7 Ohm/1000ft
18	6.6 Ohm/1000ft	

#### Capacitance:

Nom. Capacitance Conductor to Shield
15.4 pF/ft

#### Impedance:

Nominal Characteristic Impedance
100 Ohm

#### Delay:

Nominal Velocity of Propagation (VP) [%]	Nominal Velocity of Propagation (VP) Description
66 %	24 AWG

### Current:

Element	Max. Recommended Current [A]
24 AWG	2.1 A
18 AWG	4.8 A

### Voltage:

UL Voltage Rating
300 V RMS (UL AWM Style 20233)

### Use

Suitability - Sunlight Resistance:	High
Max Recommended Pulling Tension:	100 lbs

### Safety

#### Temperature Range

Operating Temp Range:	-40°C To +80°C
UL Temp Rating:	80°C (UL AWM Style 20233)

#### Mechanical Characteristics

Min Bend Radius/Minor Axis:	3 in
-----------------------------	------

#### Part Number

Plenum (Y/N):	No
---------------	----

#### Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
UL AWM Style:	AWM Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

#### History

Notes:	Oil Resistance: High
--------	----------------------

## Product Variants

Part Number	Color	Put-Up Type	Length
3119A Y5P1000	GREEN Y5P	Reel	1000 ft
3119A Y5P500	GREEN Y5P	Reel	500 ft

© 2016 Belden, Inc.

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.