



Part Number: 32720

Hook-Up/Lead Wire UL AWM Style 1015, (1) 20 AWG (7x28) Uni-Strand TC, PVC, 600V, 105° C

Product Description

One 20 AWG stranded (7x28) Uni-Strand® tinned copper conductor, PVC insulation.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	No. of Conductors
20	7x28	Uni-Strand® (TC- Tinned Copper)	1

Total Number of Conductors:	1	1
i otat Nullibel of Colluctors.	4 4	

Insulation:

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	o.o3 in

Outerjacket 1:

Nominal Diameter	
0.099 in	

Electrical Characteristics

Voltage:

UL Voltage Rating

600 V RMS (UL AWM Style 1015)

Use

Safety

UL Flammability: VW-1

Temperature Range

UL Temp Rating:	105°C (UL AWM Style 1015)
or remp kating.	105 C (OLAW M Style 1015)

Mechanical Characteristics

Part Number

Plenum (Y/N):	No	
Plenum (Y7 N):	No	

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)	
CSA Rating:	CSA Rating	
CSA Type:	CSA Type	
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)	
UL AWM Style:	UL AWM Style	
UL Rating:	UL Rating	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	

History

Product Variants

Part Number	Color	Put-Up Type	Length
32720 0134000	BLUE, DARK	Reel	4000 ft

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will, Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling storage, and any other operation of the product itself or the one that it becomes a part of. This Product