



Part Number: 49733

Molded Cable Assembly, GPIB, 1.6 ft, (6 pr) 26 AWG (7x34) TC, (10) 26 AWG (7x34) TC, (1) 24 AWG (7x32) TC, Foil Shld, Metal Backshell, S-R PVC/PVC, CM

# **Product Description**

Six 26 AWG pairs stranded (7x34) tinned copper conductors, ten 26 AWG stranded (7x34) tinned copper conductors, one 24 AWG stranded (7x32) tinned copper conductors, Beldfoil® shield plus tinned copper braid, metal backshell, S-R PVC insulation, PVC Jacket, 1.6 foot length.

# **Product Specifications**

## **Technical Specifications**

### **Construction and Dimensions**

#### Conductor:

AWG	Stranding	Material	No. of Conductors	No. of Pairs
26	7×34	TC - Tinned Copper		6
26	7×34	TC - Tinned Copper	10	
24	7×32	TC - Tinned Copper	1	

Total Number of Conductors:	23

#### Insulation:

Material	Nominal Wall Thickness
S-R PVC - Semi-Rigid Polyvinyl Chloride	0.01 in

#### Stranding:

Lay Length	
24 AWG Single mm	

#### Outershield 1:

	Туре	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
T	ape	1	Aluminum Foil-Polyester Tape	Beldfoil®	M O O %	TC - Tinned Copper	26	7×34 mm
E	Braid	2	TC - Tinned Copper		90 %			

## Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	o.35 in	o.035 in

# **Electrical Characteristics**

### Voltage:

# UL Voltage Rating 300 V RMS (UL AWM Style 2464)

## Use

## Safety

# **Temperature Range**

UL Temp Rating:	80°C (UL AWM Style 2464)
or remp kamig.	80 C (OL AW M Style 2404/

## **Mechanical Characteristics**

## **Part Number**

Plenum (Y/N):	No

# **Standards**

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)	
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)	
NEC/(UL) Specification:	NEC/(UL) Specification	
UL AWM Style:	AWM Specification	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	

# **History**

Molded connector is male/female design for easy stacking and comes with molded-in metric jackscrews.

#### **Product Variants**

Part Number	Color	Length
49733 C62S2	GRAY, GULL	1.6 ft

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.