



Part Number: 7501A

75 Ohm Flex Vision Coax, (1) 25 AWG (19x38) BC, FPE/PVC, TC Braid Shld

Product Description

One 25 AWG stranded (19x38) bare copper conductor, foam polyethylene (FPE) insulation, tinned copper french braid, Belflex jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Coax
25	19x38	BC - Bare Copper	0.019 in	1
Total Number of Conductors:				1

Insulation:

Material	Nominal Diameter
FPE - Foam Polyethylene	0.09 in

Outershield 1:

Type	Material	Coverage [%]
French Braid	TC - Tinned Copper	95 %

Outerjacket 1:

Material	Material Trade Name	Nominal Diameter
PVC Blend - Polyvinyl Chloride Blend	Belflex®	0.146 in

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
35 Ohm/1000ft	9.1 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Shield
17.7 pF/ft

Impedance:

Nominal Characteristic Impedance
75 Ohm

High Frequency (Nominal/Typical):

Frequency [MHz]	Nom. Insertion Loss
2.2 MHz	0.6 db/100ft
5 MHz	0.9 db/100ft
10 MHz	1.3 db/100ft
30 MHz	2.2 db/100ft
50 MHz	2.9 db/100ft
100 MHz	4.2 db/100ft

Delay:

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.3 ns/ft	77 %

High Freq:

Frequency [MHz]
2.2 MHz
5 MHz
10 MHz
30 MHz
50 MHz
100 MHz

Inductance:

Nominal Inductance
0.097 μ H/ft

Voltage:

UL Voltage Rating

30 V RMS (UL AWM Style 1354)

Use

Flex Cycle Rating:	1 Million
Max Recommended Pulling Tension:	22 lbs

Safety

C(UL) Flammability:	FT1
---------------------	-----

Temperature Range

Operating Temp Range:	-40°C To +80°C
-----------------------	----------------

Mechanical Characteristics

Min Bend Radius (Continuous Flexing):	3 in
Min Bend Radius/Minor Axis:	1.5 in

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CSA AWM Specification:	CSA Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
UL AWM Style:	AWM Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

History

Product Variants

Part Number	Color	Put-Up Type	Length
7501A G7X1000	BLUE, MATTE	Reel	1000 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of

such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.