



**Part Number:** 7503A

75 Ohm Flex Vision Coax, (1) 20 AWG (7x15x40) BC, FPE/PVC Blend, TC Braid Shld

## Product Description

One 20 AWG stranded (7x15x40) bare copper conductor, foam polyethylene (FPE) insulation, tinned copper french braid, Belflex jacket.

## Product Specifications

## Technical Specifications

### Construction and Dimensions

#### Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Coax
20	7x15x40	BC - Bare Copper	0.04 in	1
<b>Total Number of Conductors:</b>				1

#### Insulation:

Material	Nominal Diameter
FPE - Foam Polyethylene	0.185 in

#### Outershield 1:

Type	Material	Coverage [%]
French Braid	TC - Tinned Copper	95 %

#### Outerjacket 1:

Material	Material Trade Name	Nominal Diameter
PVC Blend - Polyvinyl Chloride Blend	Belflex®	0.275 in

## Electrical Characteristics

### Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
8.1 Ohm/1000ft	11 Ohm/1000ft

### Capacitance:

Nom. Capacitance Conductor to Shield
17.3 pF/ft

### Impedance:

Nominal Characteristic Impedance
75 Ohm

### High Frequency (Nominal/Typical):

Frequency [MHz]	Nom. Insertion Loss
2.2 MHz	0.3 db/100ft
5 MHz	0.4 db/100ft
10 MHz	0.6 db/100ft
30 MHz	1.1 db/100ft
50 MHz	1.5 db/100ft
100 MHz	2.2 db/100ft

### Delay:

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.3 ns/ft	80 %

### High Freq:

Frequency [MHz]
2.2 MHz
5 MHz
10 MHz
30 MHz
50 MHz
100 MHz

### Inductance:

Nominal Inductance
0.097 $\mu$ H/ft

### Voltage:

## UL Voltage Rating

30 V RMS (UL AWM Style 1354)

## Use

Max Recommended Pulling Tension: 35 lbs

## Safety

C(UL) Flammability: FT1

## Temperature Range

Operating Temp Range: -40°C To +80°C

## Mechanical Characteristics

Min Bend Radius (Continuous Flexing): 5.5 in

Min Bend Radius/Minor Axis: 2.75 in

## Part Number

Plenum (Y/N): No

## Standards

CA Prop 65 (CJ for Wire & Cable): CA Prop 65 (CJ for Wire & Cable)

CSA AWM Specification: CSA Specification

MII Order #39 (China RoHS): MII Order #39 (China RoHS)

RG Type: RG Type

UL AWM Style: AWM Specification

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: EU CE Mark

## History

## Product Variants

Part Number	Color	Put-Up Type	Length
7503A G7X1000	BLUE, MATTE	Reel	1000 ft
7503A G7X250	BLUE, MATTE	Reel	250 ft
7503A G7X500	BLUE, MATTE	Reel	500 ft

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.