



**Part Number:** 7931A

Cat 6 High & Low Temp DataTwist®, (4 pr) 23 AWG  
Solid BC, FEP/FEP, Gas Res, CMP

## Product Description

Four Cat 6 23 AWG Bonded-Pairs solid bare copper conductors, FEP insulation, FEP jacket.

## Product Specifications

### Technical Specifications

<b>Suitable Applications:</b>	Industrial Ethernet Cable, Harsh Environments, 350MHz Enhanced Category 6, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, RJ-45 Compatible, High and Low Temperature, Oil and Gasoline Exposure, Limited Combustible FHC 25/50
-------------------------------	---

## Construction and Dimensions

### Conductor:

AWG	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4

<b>Total Number of Conductors:</b>	8
------------------------------------	---

### Insulation:

Material
FEP - Fluorinated Ethylene Propylene

### Color Chart 1:

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

### Cabling 1:

Filler
Rod Center Member

### Outershield 1:

Material
Unshielded

### Outerjacket 1:

Material	Nominal Diameter
FEP - Fluorinated Ethylene Propylene	0.214 in

## Electrical Characteristics

### Conductor DCR:

Max. Conductor DCR	Max. DCR Unbalance
9.38 Ohm/1000ft	5 %

### Capacitance:

Max. Capacitance Unbalance	Nom.Mutual Capacitance
330 pF/ft	15 pF/ft

### Delay:

Max. Delay	Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
537 @ 100MHz ns/100m	45 ns/100m	72 %

### High Freq:

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. SRL (Structural Return Loss)	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance
1 MHz	2 db/100m	74.3 dB	72.3 dB	72.3 dB	70.3 dB	67.8 dB	64.8 dB	20 dB	na dB	100 ± 15 Ohm	
4 MHz	3.8 db/100m	65.3 dB	63.3 dB	61.5 dB	59.5 dB	55.8 dB	52.7 dB	23 dB	na dB	100 ± 15 Ohm	
8 MHz	5.3 db/100m	60.8 dB	58.8 dB	55.4 dB	53.4 dB	49.7 dB	46.7 dB	24.5 dB	na dB	100 ± 15 Ohm	
10 MHz	6 db/100m	59.3 dB	57.3 dB	53.3 dB	51.3 dB	47.8 dB	44.8 dB	25 dB	na dB	100 ± 15 Ohm	
16 MHz	7.6 db/100m	56.2 dB	54.3 dB	48.7 dB	46.7 dB	43.7 dB	40.7 dB	25 dB	na dB	100 ± 15 Ohm	
20 MHz	8.5 db/100m	54.8 dB	52.8 dB	46.3 dB	44.3 dB	41.8 dB	38.7 dB	25 dB	na dB	100 ± 15 Ohm	
25 MHz	9.5 db/100m	53.3 dB	51.3 dB	43.8 dB	41.8 dB	39.8 dB	36.8 dB	24.3 dB	na dB	100 ± 15 Ohm	
31.25 MHz	10.7 db/100m	51.9 dB	49.9 dB	41.2 dB	39.2 dB	37.9 dB	34.9 dB	23.6 dB	na dB	100 ± 15 Ohm	
62.5 MHz	15.4 db/100m	47.4 dB	45.4 dB	32 dB	30 dB	31.9 dB	28.8 dB	21.5 dB	na dB	100 ± 15 Ohm	
100 MHz	19.8 db/100m	44.3 dB	42.3 dB	24.5 dB	22.5 dB	27.8 dB	24.8 dB	20.1 dB	na dB	100 ± 15 Ohm	100 ± 15 Ohm
155 MHz	25.2 db/100m	41.5 dB	39.5 dB	16.3 dB	14.3 dB	23.9 dB	20.9 dB	18.8 dB	na dB	100 ± 22 Ohm	100 ± 15 Ohm
200 MHz	29 db/100m	39.8 dB	37.8 dB	10.8 dB	8.8 dB	21.8 dB	18.7 dB	18 dB	na dB	100 ± 22 Ohm	100 ± 15 Ohm
250 MHz	32.8 db/100m	38.3 dB	36.3 dB	5.5 dB	3.5 dB	19.8 dB	16.8 dB	17.3 dB	na dB	100 ± 32 Ohm	100 ± 15 Ohm
1 MHz											
4 MHz											
8 MHz											
10 MHz											
16 MHz											
20 MHz											
25 MHz											
31.25 MHz											
62.5 MHz											
100 MHz											
155 MHz											
200 MHz											
250 MHz											

**Voltage:**

**UL Voltage Rating**

300 V RMS

**Use**

Suitability - Oil Resistance:	Yes
Max Recommended Pulling Tension:	40 lbs

## Safety

CSA Flammability:	FT6
UL Flammability:	UL723 (NFPA 255), NFPA 262

## Temperature Range

Installation Temp Range:	-55°C To +150 °C
Operating Temp Range:	-70°C To +150°C

## Mechanical Characteristics

Min Bend Radius/Minor Axis:	0.5 in
-----------------------------	--------

## Part Number

Plenum (Y/N):	Yes
---------------	-----

## Standards

Telecommunications Standards:	Telecommunications Standards
CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CEC/C(UL) Specification:	CEC/C(UL) Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC Articles:	NEC Articles
NEC/(UL) Specification:	NEC/(UL) Specification
Other Specification:	Other Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)

## History

Notes:	US Patents 5, 606, 151& 5, 573, 126. Operating temperatures subject to length de-rating.
--------	--

## Product Variants

Part Number	Color	Put-Up Type	Length
7931A 0101000	BLACK	Reel	1000 ft

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.