



**Part Number:** 7953A

Cat 6 600V DataTuff®, (4 pr) 23 AWG Solid BC, PP/PVC/PVC, Foil Shld, CMR, CMX-Outdoor

## Product Description

Four Cat 6 23 AWG solid bare copper conductors, bonded pair polypropylene insulation, FRPE spline center member, inner PVC jacket, overall Beldfoil® Shield (100% coverage), DataTuff® PVC outer jacket.

## Product Specifications

## Technical Specifications

<b>Suitable Applications:</b>	Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155 ATM, 622 ATM, 250MHz Category 6
-------------------------------	--

## Construction and Dimensions

### Conductor:

Element	AWG	Stranding	Material	No. of Pairs
	23	Solid	BC - Bare Copper	4
No Ground				

<b>Total Number of Conductors:</b>	8
------------------------------------	---

### Insulation:

Material	Nominal Diameter	Nominal Wall Thickness
PP - Polypropylene	0.043 in	0.01 in

### Color Chart 1:

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

### Stranding:

Lay Length
N mm

### Innerjacket:

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC	0.27 in	0.02 in	Yes

### Cabling 1:

Filler
X-Spline Center Member

### Outershield 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	24	7x32 mm

### Outerjacket 1:

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord
Industrial Grade PVC - Polyvinyl Chloride	Datatuff®	0.335 in	0.03 in	No
		0.335 in		

<b>Print Legend:</b>	7953A BELDEN VERIFIED (UL) CAT 6 4PR23 E108998-M CMR-CMX OUTDOOR OR C(UL) CMG----ISO/IEC11801 CAT 6 --- 300V PATENTED OIL/SUN RES FT4 IEEE 1202 123456 FT
----------------------	---

## Electrical Characteristics

### Conductor DCR:

Max. Conductor DCR	Max. DCR Unbalance
8.2 Ohm/1000ft	3 %

### Capacitance:

Max. Capacitance Unbalance	Nom.Mutual Capacitance
330 pF/ft	15 pF/ft

### Delay:

Max. Delay	Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
537 @ 100MHz ns/100m	45 ns/100m	72 %

### High Freq:

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. SRL (Structural Return Loss)	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance
1 MHz	2 db/100m	74.3 dB	72.3 dB	72.3 dB	70.3 dB	67.8 dB	64.8 dB	21 dB	na dB	100 ± 15 Ohm	
4 MHz	3.8 db/100m	65.3 dB	63.3 dB	61.5 dB	59.5 dB	55.8 dB	52.7 dB	24 dB	na dB	100 ± 15 Ohm	
8 MHz	5.3 db/100m	60.8 dB	58.8 dB	55.4 dB	53.4 dB	49.7 dB	46.7 dB	25.5 dB	na dB	100 ± 15 Ohm	
10 MHz	6 db/100m	59.3 dB	57.3 dB	53.3 dB	51.3 dB	47.8 dB	44.8 dB	26 dB	na dB	100 ± 15 Ohm	
16 MHz	7.6 db/100m	56.2 dB	54.3 dB	48.7 dB	46.7 dB	43.7 dB	40.7 dB	26 dB	na dB	100 ± 15 Ohm	
20 MHz	8.5 db/100m	54.8 dB	52.8 dB	46.3 dB	44.3 dB	41.8 dB	38.8 dB	26 dB	na dB	100 ± 15 Ohm	
25 MHz	9.5 db/100m	53.3 dB	51.3 dB	43.8 dB	41.8 dB	39.8 dB	36.8 dB	25.3 dB	na dB	100 ± 15 Ohm	
31.25 MHz	10.7 db/100m	51.9 dB	49.9 dB	41.2 dB	39.2 dB	37.9 dB	34.9 dB	24.6 dB	na dB	100 ± 15 Ohm	
62.5 MHz	15.4 db/100m	47.4 dB	45.4 dB	32 dB	30 dB	31.9 dB	28.9 dB	22.5 dB	na dB	100 ± 15 Ohm	
100 MHz	19.8 db/100m	44.3 dB	42.3 dB	24.5 dB	22.5 dB	27.8 dB	24.8 dB	21.1 dB	na dB	100 ± 15 Ohm	100 ± 15 Ohm
155 MHz	25.2 db/100m	41.5 dB	39.5 dB	16.3 dB	14.3 dB	23.9 dB	20.9 dB	19.8 dB	na dB	100 ± 22 Ohm	100 ± 15 Ohm
200 MHz	29 db/100m	39.8 dB	37.8 dB	10.8 dB	8.8 dB	21.8 dB	18.8 dB	19 dB	na dB	100 ± 22 Ohm	100 ± 15 Ohm
250 MHz	32.8 db/100m	38.3 dB	36.3 dB	5.5 dB	3.5 dB	19.8 dB	16.8 dB	18.3 dB	na dB	100 ± 32 Ohm	100 ± 15 Ohm
1 MHz											
4 MHz											
8 MHz											
10 MHz											
16 MHz											
20 MHz											
25 MHz											
31.25 MHz											
62.5 MHz											
100 MHz											
155 MHz											
200 MHz											
250 MHz											

### Voltage:

UL Description	UL Voltage Rating
	300 V RMS
Appliance Wiring Material	600 V RMS

## Use

Suitability - Oil Resistance:	Yes
Suitability - Aerial:	Yes
Suitability - Burial:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	40 lbs

## Safety

C(UL) Flammability:	FT4
IEEE Flammability:	1202
UL Flammability:	UL1666 Riser

## Temperature Range

Installation Temp Range:	-25°C To +75°C
Operating Temp Range:	-40°C To +75°C
Storage Temp Range:	-40°C To +80°C
UL Temp Rating:	75°C

## Mechanical Characteristics

Min Bend Radius/Minor Axis:	4 in
-----------------------------	------

## Part Number

Plenum (Y/N):	No
---------------	----

## Standards

ISO/IEC Compliance:	Other Standards
Telecommunications Standards:	Telecommunications Standards
CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CEC/C(UL) Specification:	CEC/C(UL) Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)

<b>NEC/(UL) Specification:</b>	NEC/(UL) Specification
<b>Other Specification:</b>	Other Specification
<b>UL AWM Style:</b>	AWM Specification
<b>EU Directive Compliance:</b>	EU Directive 2003/11/EC (BFR)
<b>EU CE Mark:</b>	EU CE Mark

## History

<b>Notes:</b>	US Patent #'s 5,606,151; 5,734,126. Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581. Not intended for 600 V electrical power delivery.
---------------	--

## Product Variants

Part Number	Color	Put-Up Type	Length
7953A 0021000	RED	Reel	1000 ft
7953A 0061000	BLUE	Reel	1000 ft
7953A 0081000	GRAY	Reel	1000 ft
7953A 0101000	BLACK	Reel	1000 ft
7953A 0105000	BLACK	Reel	5000 ft
7953A 1NH1000	TEAL	Reel	1000 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.