



Part Number: 8024

Bus Bar Wire, (1) 28 AWG Solid TC

Product Description

One 28 AWG solid tinned copper conductor.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

| AWG | Stranding | Material | No. of Conductors |
|-----------------------------|-----------|--------------------|-------------------|
| 28 | Solid | TC - Tinned Copper | 1 |
| Circular Mil Area (CMA)1: | | | 164 |
| Total Number of Conductors: | | | 1 |

Outerjacket 1:

| Nominal Diamete | | | |
|-----------------|--|--|--|
| 0.013 in | | | |

Electrical Characteristics

Conductor DCR:

| Nominal Conductor DO | R | | |
|----------------------|---|--|--|
| 65.3 Ohm/1000ft | | | |

Safety

Temperature Range

Mechanical Characteristics

Part Number

| Dianum (V / NI) | No | |
|-----------------|------|--|
| Plenum (Y/N): | ∥ No | |
| | | |

Standards

| CA Prop 65 (CJ for Wire & Cable): | CA Prop 65 (CJ for Wire & Cable) | |
|-----------------------------------|----------------------------------|--|
| MII Order #39 (China RoHS): | MII Order #39 (China RoHS) | |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) | |

History

Product Variants

| Part Number | Color | Put-Up Type | Length |
|--------------|-------|-------------|---------|
| 8024 0001000 | NONE | Reel | 1000 ft |
| 8024 000100 | NONE | Reel | 100 ft |

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information provided in this Product Disclosure is designed only as a general guide for the safe handling storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.