



Part Number: 83393

Control/Instrumentation, (2) 20 AWG (7x28) TC, FEP/Silicone Rubber, Foil+Nylon Shld

Product Description

Two 20 AWG stranded (7x28) tinned copper conductors, Teflon® (FEP) insulation, noise reducing tape, overall Beldfoil® shield (100% coverage), silicone rubber jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	No. of Conductors
20	7x28	TC - Tinned Copper	2
Total Number of Conductors:			2

Insulation:

Material	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	0.02 in

Color Chart 1:

Number	Color
1	Black
2	Red

Cabling 1:

Lay Length	Lay Direction	Twists	Filler
1.625 in	Left Hand	7.4 twist/ft	Fiberglass yarn

Outershield 1:

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	20	7x28 mm
Tape	1	Noise Reducing Conductive Nylon					

Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness
Silicone Rubber	0.242 in	0.037 in

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR
10.5 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
22 pF/ft	40 pF/ft

Current:

Element	Max. Recommended Current [A]
10C Temperature Rise	3.8 Amps per conductor @ 25°C ambient

Inductance:

Nominal Inductance
0.2 µH/ft

Voltage:

Description	UL Description	UL Voltage Rating	Voltage Rating [V]
Shield to ground through jacket	UL AWM 4516	600 V RMS	2000 V DC

Use

Suitability - Indoor:	Yes
Max Recommended Pulling Tension:	25.2 lbs

Safety

UL Flammability:	VW -1 (Singles)
------------------	-----------------

Temperature Range

Operating Temp Range:	-70°C To +150°C
-----------------------	-----------------

Mechanical Characteristics

Min Bend Radius / Minor Axis:	2.5 in
-------------------------------	--------

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
Other Specification:	Other Specification
UL AWM Style:	AWM Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

History

Product Variants

Part Number	Color	Put-Up Type	Length
83393 004500	YELLOW	Reel	500 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.