



**Part Number:** 8455

Portable Cordage, (3) 20 AWG (26x34) TC, (2) 18 AWG (41x34) TC, EPDM/Rubber, 300V, 60°C

## Product Description

Three 20 AWG stranded (26x34) tinned copper conductors, two 18 AWG stranded (41x34) tinned copper conductors, EPDM insulation, rubber jacket.

## Product Specifications

## Technical Specifications

### Construction and Dimensions

#### Conductor:

AWG	Stranding	Material	No. of Conductors
20	26x34	TC - Tinned Copper	3
18	41x34	TC - Tinned Copper	2
<b>Total Number of Conductors:</b>			5

#### Insulation:

Material	Nominal Wall Thickness
EPDM - Ethylene Propylene Diene Monomer Rubber	0.018 in

#### Color Chart 1:

Number	Color
1	Brown
2	Green
3	White
4	Black
5	Red

### Stranding:

Lay Length
Black mm

### Cabling 1:

Filler
Jute

### Outershield 1:

Material
Unshielded

### Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness	Separator Material
Rubber	0.28 in	0.031 in	Paper Tape

<b>Print Legend:</b>	BELDEN 8455 (UL logo) AWM 4256 E12683
----------------------	---------------------------------------

## Electrical Characteristics

### Current:

Element	Max. Recommended Current [A]
20 AWG	4 Amps
18 AWG	5.6 Amps

### Voltage:

Dielectric Withstand Voltage	UL Voltage Rating
1500 V AC Applied for 1 Min.	300 V RMS

## Use

## Safety

## Temperature Range

UL Temp Rating:	60°C (UL AWM Style 4256)
-----------------	--------------------------

## Mechanical Characteristics

Min Bend Radius/Minor Axis:	3 in
-----------------------------	------

## Part Number

Plenum (Y/N):	No
---------------	----

## Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
UL AWM Style:	AWM Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

## History

## Product Variants

Part Number	Color	Put-Up Type	Length
8455 010250	BLACK	Reel	250 ft
8455 010U1000	BLACK	Reel	1000 ft
8455 010U500	BLACK	Reel	500 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an 'AS IS' basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.