



Part Number: 8471

Audio/Control/Instrumentation, (1 pr) 16 AWG (19x29) TC, PVC/PVC, CMG

Product Description

One 16 AWG pair stranded (19x29) tinned copper conductors, twisted pair, PVC insulation, PVC jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material		No. of Pairs
16	19x29	TC - Tinned Copper		1
Total Number of	Conductors:		2	

Insulation:

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.023 in

Color Chart 1:

Number	Color
1	Black & White

Innershield:

Material	
Unshielded	

Cabling 1:

Lay Length	Lay Direction	Twists
2 in	Left Hand	6 twist/ft

Outershield 1:

Material	
Unshielded	

Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.274 in	0.032 in

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR	
4.49 Ohm/1000ft	

Capacitance:

Nom. (Capacitance Conductor to Conductor
33 pF/f	ft

Current:

Element	Max. Recommended Current [A]
10C temperature rise	6.1 Amps per conductor @ 25°C ambient

Inductance:

Nominal Inductance	
0.19 µH/ft	

Voltage:

UL Voltage Rating		
300 V RMS		

Use

Suitability - Indoor:	Yes
Max Recommended Pulling Tension:	61 lbs

Safety

CSA Flammability:	FT4

UL Flammability:	UL1685 FT4 Loading
------------------	--------------------

Temperature Range

Non-UL Temp Rating: 60°C (UL AWM Style 2598)	
Operating Temp Range:	-20°C To +80°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	2.75 in
-----------------------------	---------

Part Number

Plenum (Y/N):	Νο

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)	
CEC/C(UL) Specification:	CEC/C(UL) Specification	
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)	
NEC Articles:	NEC Articles	
NEC/(UL) Specification:	NEC/(UL) Specification	
UL AWM Style:	AWM Specification	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	EU CE Mark	

History

Product Variants

Part Number	Color	Put-Up Type	Length
8471 0601000	CHROME	Reel	1000 ft
8471 0605000	CHROME	Reel	5000 ft
8471 060500	CHROME	Reel	500 ft
8471 060U1000	CHROME	UnReel	1000 ft
8471 060U500	CHROME	UnReel	500 ft
8471.00305	CHROME	Reel	305 ft
8471.00U152	CHROME	UnReel	152 ft
8471.00U305	CHROME	UnReel	305 ft
8471.011525	CHROME	Reel	1525 ft
8471.01152	CHROME	Reel	152 ft
8471.01153	CHROME	Reel	153 ft
8471NH 010500	BLACK	Reel	500 ft

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Part # PF_8471 | Page 4 of 4 | May 25, 2016

Belden Inc. | belden.catalog.belden.com/en/Products/Detail/PF_8471