



#### Part Number: 85241

Control/Instrumentation, (3) 16 AWG (19x29) TC, ETFE/ETFE, Alum Foil Shld

# **Product Description**

Three 16 AWG stranded (19x29) tinned copper conductors, Tefzel® (ETFE) insulation, overall Aluminum-Kapton® shield (100% coverage), Tefzel® (ETFE) jacket.

# **Product Specifications**

# **Technical Specifications**

## **Construction and Dimensions**

#### Conductor:

AWG	Stranding	Material		No. of Conductors
16	19x29	TC - Tinned Copper		3
Total Number o	f Conductors:		3	

#### Insulation:

Material	Material Trade Name	Nominal Wall Thickness
ETFE - Ethylene Tetrafluoroethylene	Tefzel®	0.014 in

### Color Chart 1:

Nun	nber	Color
1		Black
2		Red
3		Green

### Outershield 1:

Туре	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Таре	Aluminum-Kapton® Foil	100 %	TC - Tinned Copper	18	Stranded mm

### Outerjacket 1:

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
ETFE - Ethylene Tetrafluoroethylene	Tefzel®	0.225 in	0.02 in

## Electrical Characteristics

### Conductor DCR:

Nominal Conductor	CR		
4.27 Ohm/1000ft			

## Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
34 pF/ft	61.2 pF/ft

### Current:

Max. Recommended Current [A]	
7 Amps per conductor @ 25°C	

### Voltage:

Non-UL Voltage Rating	
300 V RMS	

## Use

Max Recommended Pulling Tension:	90 lbs

## Safety

UL Flammability:	VW-1

# Temperature Range

Non-UL Temp Rating:	150°C
Operating Temp Range:	-60°C To +150°C

# Mechanical Characteristics

Min Bend Radius/Minor Axis:	2.25 in

## Part Number

Plenum (Y/N):	No
---------------	----

**Standards** 

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
Other Specification:	Other Specification
EU Directive Compliance: EU Directive 2003/11/EC (BFR)	
EU CE Mark:	EU CE Mark

## **History**

Notes:	Tefzel and Kapton are DuPont trademarks.

# **Product Variants**

Part Number	Color	Put-Up Type	Length
85241 3681000	CLEAR, TRANSPARENT	Reel	1000 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Part # PF\_85241 | Page 3 of 3 | May 25, 2016

Belden Inc. | belden.catalog.belden.com/en/Products/Detail/PF\_85241