



Part Number: 8641

Single-Pair, (1 pr) 24 AWG (7x32) TC, PE/PVE, Foil Shld,

CM

## **Product Description**

One 24 AWG pair stranded (7x32) tinned copper conductors, twisted pair, polyethylene insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

# **Product Specifications**

## **Technical Specifications**

## **Construction and Dimensions**

#### Conductor:

AWG	Stranding	Material	No. of Pairs
24	7×32	TC - Tinned Copper	1
Total Number of Conductors:		2	

#### Insulation:

Material	Nominal Wall Thickness
PE - Polyethylene	0.017 in

#### Color Chart 1:

Number	Color
1	Black & Clear

#### Outershield 1:

Туре	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	24	7x32 mm

## Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	o.168 in	0.025 in

## **Electrical Characteristics**

## **Conductor DCR:**

Nominal Conductor DCR	Nominal Outer Shield DCR
25 Ohm/1000ft	14.6 Ohm/1000ft

## Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
22 pF/ft	42 pF/ft

#### Impedance:

Nominal Characteristic Impedance	
80 Ohm	

#### **Current:**

Max. Recom	mended Current [A]	
2.2 Amps per	conductor @ 25°C	

#### Inductance:

Nominal Inductance	
0.22 μH/ft	

## Voltage:

UL Voltage Rating	
300 V RMS (UL AWM Style 2092)	

## Use

Max Recommended Pulling Tension:	11 lbs

## Safety

UL Flammability:	UL1685 UL Loading
------------------	-------------------

## **Temperature Range**

Operating Temp Range:	-20°C To +80°C
UL Temp Rating:	60°C (UL AWM Style 2092)

## **Mechanical Characteristics**

Min Bend Radius/Minor Axis:	1.75 in
-----------------------------	---------

## **Part Number**

Plenum (Y/N):	No
Plenum Number:	88641, 82641

## **Standards**

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)	
CEC/C(UL) Specification:	CEC/C(UL) Specification	
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)	
NEC/(UL) Specification:	NEC/(UL) Specification	
UL AWM Style:	AWM Specification	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	EU CE Mark	

## **History**

## **Product Variants**

Part Number	Color	Put-Up Type	Length
8641 0601000	CHROME	Reel	1000 ft
8641 060100	CHROME	Reel	100 ft
8641 0605000	CHROME	Reel	5000 ft
8641 060500	CHROME	Reel	500 ft
8641 060U1000	CHROME	UnReel	1000 ft
8641 060U500	CHROME	UnReel	500 ft

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.