



Part Number: 8718 Single-Pair, (1 pr) 12 AWG (19x25) TC, PE/PVC, Foil Shld

Product Description

One 12 AWG pair stranded (19x25) TC conductors, twisted pair, polyethylene insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material		No. of Pairs
12	19x25	TC - Tinned Coppe	r	1
Total Number of (Conductors:		2	

Insulation:

Material	Nominal Wall Thickness
PE - Polyethylene	0.037 in

Color Chart 1:

Number	Color
1	Black & Clear

Outershield 1:

Туре	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Таре	Aluminum Foil-Polyester Tape	Beldfoil® (Z-Fold®)	100 %	TC - Tinned Copper	14	Stranded mm

Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.4 in	0.034 in

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR	
1.6 Ohm/1000ft	

Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
25 pF/ft	49 pF/ft

Impedance:

Nominal C	haracteristic Impedance
55 Ohm	

Current:

Max. Recommended Current [A]	
12.5 Amps per conductor @ 25°C	

Inductance:

Nominal Inducta	ce	
o.2 µH∕ft		

Voltage:

UL Description	UL Voltage Rating
ULAWM	600 V RMS
CSA AWM	300 V RMS

Use

Max Recommended Pulling Tension:	225 lbs

Safety

CSA Flammability:	FT1

- Flammability:	UL1685 UL Loading
-----------------	-------------------

Temperature Range

Operating Temp Range:	-20°C To +80°C
UL Temp Rating:	80°C (UL AWM Style 20253)

Mechanical Characteristics

Min Bend Radius/Minor Axis:	4 in
-----------------------------	------

Part Number

Plenum (Y/N):	Νο

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)	
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)	
NEC/(UL) Specification:	NEC/(UL) Specification	
Other Specification:	Other Specification	
UL AWM Style:	AWM Specification	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	EU CE Mark	

History

Product Variants

Part Number	Color	Put-Up Type	Length
8718 0601000	CHROME	Reel	1000 ft
8718 0602000	CHROME	Reel	2000 ft
8718 0605000	CHROME	Reel	5000 ft
8718 060500	CHROME	Reel	500 ft
8718 060U500	CHROME	UnReel	500 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its

publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Part # PF_8718 | Page 4 of 4 | May 25, 2016 Belden Inc. | belden.catalog.belden.com/en/Products/Detail/PF_8718