



Part Number: 89182

Twinax, (1 pr) 22 AWG (19x34) TC, FFEP/FEP, Foil Shld, CMP

Product Description

One 22 AWG pair stranded (19x34) tinned copper conductors, Teflon® (FFEP) insulation, Duofoil® (100% coverage), Teflon® (FEP) jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
22	19X34	TC - Tinned Copper	0.031 in	1
Total Number of Conductors:				2

Insulation:

Material	Material Trade Name	Nominal Diameter
FFEP - Foam Fluorinated Ethylene Propylene	Teflon®	0.278 in

Color Chart 1:

Number	Color
1	Black & Yellow

Stranding:

Lay Length	Lay Direction	Twists	Diameter
3 in	Left Hand	4 twist/ft	0.278 mm

Outershield 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	Duofoil®	100 %	TC - Tinned Copper	22	19x34 mm

Outerjacket 1:

Material	Material Trade Name	Nominal Diameter
FEP - Fluorinated Ethylene Propylene	Teflon®	0.307 in

Electrical Characteristics**Conductor DCR:**

Nominal Conductor DCR	Nominal Outer Shield DCR
14 Ohm/1000ft	6.3 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
8.8 pF/ft	16.5 pF/ft

Impedance:

Nominal Characteristic Impedance
150 Ohm

High Frequency (Nominal/Typical):

Nom. Insertion Loss
0.4 db/100ft
1.2 db/100ft
2.7 db/100ft
4.3 db/100ft
6.2 db/100ft
8.8 db/100ft

Delay:

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.3 ns/ft	78 %

High Freq:

Frequency [MHz]
1 MHz
10 MHz
50 MHz
100 MHz
200 MHz
400 MHz

Inductance:

Nominal Inductance
0.29 μ H/ft

Voltage:

UL Voltage Rating
300 V RMS (CMP)
150 V RMS (CL2P)

Use

Max Recommended Pulling Tension:	28 lbs
----------------------------------	--------

Safety

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262

Temperature Range

Operating Temp Range:	-70°C To +200°C
-----------------------	-----------------

Mechanical Characteristics

Min Bend Radius/Minor Axis:	3.5 in
-----------------------------	--------

Part Number

Plenum (Y/N):	Yes
Non-Plenum Number:	9182

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CEC/C(UL) Specification:	CEC/C(UL) Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)

History

Notes:

Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc. Other Maximum Continuous Currents: 2.9 Amps per conductor @ 25°C

Product Variants

Part Number	Color	Put-Up Type	Length
89182 0085000	GRAY	Reel	5000 ft
89182 0101000	BLACK	Reel	1000 ft
89182 010100	BLACK	Reel	100 ft
89182 0105000	BLACK	Reel	5000 ft
89182 010500	BLACK	Reel	500 ft
89182 0605000	CHROME	Reel	5000 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.