



Part Number: 9156NH

GreenChoice, (2 pr) 18 AWG (16x30) TC, PP/LSZH, CMG

Product Description

Two 18 AWG pair stranded (16x30) tinned copper conductors, twisted pairs, polypropylene insulation, low smoke zero-halogen jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	No. of Pairs
18	16x30	TC - Tinned Copper	2
Total Num	ber of Conductors:	4	

Insulation:

Material	Nominal Wall Thickness
PP - Polypropylene	0.013 in

Color Chart 1:

Number	Color
1	Black & Red
2	Black & White

Innershield:

Material

Unshielded

Outershield 1:

Material

Unshielded

Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness
LSZH - Low Smoke Zero Halogen	o.333 in	0.033 in

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR

5.86 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Conductor

17.5 pF/ft

Current:

Max. Recommended Current [A]

3.9 Amps per conductor @ 20°C

Voltage:

UL Voltage Rating

300 V RMS (UL AWM Style 2464)

Use

Suitability - Indoor:	Yes
Max Recommended Pulling Tension:	90 lbs

Safety

C(UL) Flammability:	FT4
UL Flammability:	UL1685 FT4 Loading
Suitability - Non-Halogenated:	Yes

Temperature Range

Operating Temp Range:	-20°C To +80°C
UL Temp Rating:	80°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	3.25 in
-----------------------------	---------

Part Number

Plenum (Y/N):	No

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)	
CEC/C(UL) Specification:	CEC/C(UL) Specification	
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)	
NEC/(UL) Specification:	NEC/(UL) Specification	
Other Specification:	Other Specification	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	EU CE Mark	

History

Product Variants

Part Number	Color	Put-Up Type	Length
9156NH 0101000	BLACK	Reel	1000 ft
9156NH 010500	BLACK	Reel	500 ft

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis with no representations or warranties whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in comptiance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

 $Belden\ declares\ this\ product\ to\ be\ in\ compliance\ with\ EU\ LVD\ (Low\ Voltage\ Directive\ 73/23/EEC), as\ amended\ by\ directive\ 93/68/EEC$