



Product Description

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material		No. of Conductors
22	7×30	TC - Tinned Copper		1
Total Number o	of Conductors:		1	

Insulation:

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.01 in

Outerjacket 1:

Nominal Diameter	
0.05 mm	

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
15 Ohm/km	6.5 Ohm/km
6.5 Ohm/1000ft	
6.5 Ohm/1000ft	
6.5 Ohm/1000ft	

High Frequency (Nominal/Typical):

Nom. Insertion Loss	
6.5 db/100m	

High Freq:

Max. Insertion Loss (/	ttenuation)	
6.5 db/100m		

Current:

Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient	10 amps

Voltage:

Description	Voltage Rating [V]
Mil-W-16878/4	600 V RMS

Use

Safety

CSA Flammability:	FT1
UL Flammability:	VW-1

Temperature Range

Operating Temp Range:	-20°C To +80°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	6.5 in

Part Number

Plenum (Y/N):	No

Standards

CA Prop 65 (CJ for Wire & Cable):	Yes	

CSA Rating:	300V RMS, 80°C	
СSA Туре:	AWM I, A/B	
MII Order #39 (China RoHS):	Yes	
UL Rating:	300V RMS, 80°C	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	Yes	

History

Product Variants

Part Number	Color	Put-Up Type	Length
9983 0011000	BROWN	Reel	1000 ft
9983 001100	BROWN	Reel	100 ft
9983 0021000	RED	Reel	1000 ft
9983 002100	RED	Reel	100 ft
9983 0031000	ORANGE	Reel	1000 ft
9983 003100	ORANGE	Reel	100 ft
9983 0041000	YELLOW	Reel	1000 ft
9983 004100	YELLOW	Reel	100 ft
9983 0051000	GREEN, DARK	Reel	1000 ft
9983 005100	GREEN, DARK	Reel	100 ft
9983 0071000	VIOLET	Reel	1000 ft
9983 0081000	GRAY	Reel	1000 ft
9983 0091000	WHITE	Reel	1000 ft
9983 009100	WHITE	Reel	100 ft
9983 01010000	BLACK	Reel	10000 ft
9983 0101000	BLACK	Reel	1000 ft
9983 010100	BLACK	Reel	100 ft
9983 0131000	BLUE, DARK	Reel	1000 ft
9983 013100	BLUE, DARK	Reel	100 ft

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product listef or the ant of this Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Part # PF_9983 | Page 4 of 4 | May 25, 2016 Belden Inc. | belden.catalog.belden.com/en/Products/Detail/PF_9983