



**Part Number: 1592A**

**CAT5e Patch, 4pr, UTP, PVC Jkt, CM**

### Product Description

CAT5e (200MHz), 4-Pair, U/UTP-unshielded, CM Rated, Premise Patch cable, 24 AWG stranded (7x32) Bare Copper conductors, polyolefin insulation, PVC jacket, RJ-45 compatible

### Technical Specifications

#### Product Overview

Environmental Space:	Indoor
Suitable Applications:	Premise Patch Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422

#### Physical Characteristics (Overall)

##### Conductor

AWG	Stranding	Material	No. of Pairs
24	7x32	BC - Bare Copper	4

Conductor Count:	8
Total Number of Pairs:	4
Conductor Size:	24 AWG

##### Insulation

Material
PO - Polyolefin

##### Color Chart

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

##### Outer Jacket Material

Material	Nominal Diameter	Ripcord
PVC - Polyvinyl Chloride	0.213 in	No

#### Electrical Characteristics

##### Conductor DCR

Max. Conductor DCR	Max. DCR Unbalance
9.38 Ohm/100m	3 %

##### Capacitance

Max. Capacitance Unbalance	Nom. Mutual Capacitance
330 pF/100m	15 pF/ft

Shielding:	U/UTP - Unshielded
------------	--------------------

##### Delay

Max. Delay	Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]	Typical Delay Skew
@ 100 MHz 537.6 ns/100m	45 ns/100m	69 %	37 ns/100m

## High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance
1 MHz	2.4 dB/100m	65.3 dB	62.3 dB	63.8 dB	60.8 dB	20.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
4 MHz	4.9 dB/100m	56.3 dB	53.3 dB	51.7 dB	48.7 dB	23.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
8 MHz	6.9 dB/100m	51.8 dB	48.8 dB	45.7 dB	42.7 dB	24.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
10 MHz	7.8 dB/100m	50.3 dB	47.3 dB	43.8 dB	40.8 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
16 MHz	9.9 dB/100m	47.3 dB	44.2 dB	39.7 dB	36.7 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
20 MHz	11.1 dB/100m	45.8 dB	42.8 dB	37.7 dB	34.7 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
25 MHz	12.5 dB/100m	44.3 dB	41.3 dB	35.8 dB	32.8 dB	24.3 dB	100 ± 15 Ohm	100 ± 15 Ohm
31.25 MHz	14.1 dB/100m	42.9 dB	39.9 dB	33.9 dB	30.9 dB	23.6 dB	100 ± 15 Ohm	100 ± 15 Ohm
62.5 MHz	20.4 dB/100m	38.4 dB	35.4 dB	27.8 dB	24.8 dB	21.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
100 MHz	26.4 dB/100m	35.3 dB	32.3 dB	23.8 dB	20.8 dB	20.1 dB	100 ± 15 Ohm	100 ± 15 Ohm
155 MHz	33.7 dB/100m	32.5 dB	29.4 dB	19.9 dB	16.9 dB	15.8 dB	100 ± 25 Ohm	100 ± 15 Ohm
200 MHz	38.9 dB/100m	30.8 dB	27.8 dB	17.7 dB	14.7 dB	15.0 dB	100 ± 25 Ohm	100 ± 15 Ohm

## Voltage

<b>UL Voltage Rating</b>
300V RMS

## Temperature Range

Installation Temp Range:	0°C To +50°C
UL Temp Rating:	75°C
Storage Temp Range:	-20°C To +75°C
Operating Temp Range:	-20°C To +75°C

## Mechanical Characteristics

Bulk Cable Weight:	21 lbs/1000ft
Max Recommended Pulling Tension:	25 lbs
Min Bend Radius/Minor Axis:	1.0 in
Min Bend Radius/Installation:	2.25 in

## Standards

NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
ISO/IEC Compliance:	11801 ed 2.2 (2011) Class D Patch
Data Category:	Category 5e
ANSI Compliance:	S-90-661-2012 Category 5e Patch, ANSI/NEMA WC-63.1 Category 5e Patch
Telecommunications Standards:	ANSI/TIA-568-C.2 Category 5e Patch
IEEE Specification:	POE per 802.3af & POE+ per 802.3at-2009
Third Party Performance Verification:	Category 5e Patch

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	Yes
EU CE Mark:	Yes
EU REACH SVHC Compliance (yyyy-mm-dd):	2017-07-10
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Aerial:	No
Suitability - Burial:	No

Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	No
Suitability - Oil Resistance:	No
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

## Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT1
UL Flammability:	UL 1685 (UL 1581) Vertical Tray
UL Voltage Rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color	Footnote
1592A 0101000	BLACK	C
1592A 010U1000	BLACK	
1592A 0061000	BLUE	C
1592A 006U1000	BLUE	
1592A F2V1000	GRAY	
1592A F2VU1000	GRAY	
1592A 0051000	GREEN	C
1592A 005U1000	GREEN	
1592A 0031000	ORANGE	C
1592A 003U1000	ORANGE	
1592A 0071000	PURPLE	C
1592A 007U1000	PURPLE	
1592A 0021000	RED	C
1592A 002U1000	RED	
1592A 0091000	WHITE	C
1592A 009U1000	WHITE	
1592A 0041000	YELLOW	
1592A 004U1000	YELLOW	

Footnote:	C - CRATE REEL PUT-UP.
Patent:	<a href="http://www.belden.com/p">http://www.belden.com/p</a>

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.