


Part Number: 1812A





Product Description

24 AWG stranded (42x40) high-conductivity BC conductors, PVC insulation, double bare copper spiral shield (95% coverage), PVC outer jacket.

Technical Specifications

Product Overview

Environmental Space:			Indoor (Not R	iser or Plenum)	
hys	ical Char	acteristics (Overall)			
Conductor					
AWG	Stranding	Material	Nomi	nal Diameter	No. of Conductors
	42x40	High Conductivity BC - Bare Copper	0.024	in	2
24					
	ictor Count:			2	

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.047 in	0.0115 in

Inner Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.122 in	0.013 in

Outer Shield Material

Туре	Material	Coverage [%]
Double Spiral Serve	BC - Bare Copper	95 %

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.213 in	0.037 in
	0.037 in	

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR
23.3 Ohm/1000ft	23.3 Ohm/1000ft	5.3 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
33 pF/ft	54 pF/ft
Shielding:	Serve(s) or Spiral(s)

Inductance

Nominal Inductance

Voltage



Temperature Range

Non-UL Temp Rating:	60°C
Operating Temp Range:	-30°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	30 lbs/1000ft
Max Recommended Pulling Tension:	10 lbs
Min Bend Radius/Minor Axis:	2.25 in

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No

Part Number

Variants

Item #	Color	Footnote
1812A B591000	BLACK, MATTE	С
1812A B59328	BLACK, MATTE	
1812A B59N1000	BLACK, MATTE	
1812A B59N1000	BLACK, MATTE	
1812A G7X1000	BLUE, MATTE	С
1812A G7XN1000	BLUE, MATTE	
1812A G7XN1000	BLUE, MATTE	
1812A G7W1000	GREEN, MATTE	
1812A G7WN1000	GREEN, MATTE	
1812A G7WN1000	GREEN, MATTE	
1812A G7V328	RED, MATTE	
1812A G7VN1000	RED, MATTE	
1812A G7VN1000	RED, MATTE	

Footnote: C - CRATE REEL PUT-UP.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.