

**Part Number: 5002UP**



Commercial Audio, 4 Conductor 12 AWG BC, CL3

**Product Description**

Commercial Audio Cable, 4 Conductor 12 AWG, highly flexible stranded (65x30) bare copper conductors with PVC insulation, CL3, PVC jacket with ripcord.

**Technical Specifications**

**Product Overview**

Environmental Space:	Indoor (Not Riser or Plenum)
----------------------	------------------------------

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	No. of Conductors
12	65x30	Bare High-Conductivity ETP Copper	4
Conductor Count:			4
Conductor Size:			12 AWG

**Insulation**

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.02 in

**Color Chart**

Color
Black
White
Red
Green

**Outer Shield Material**

Material
Unshielded

**Outer Jacket Material**

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.365 in	0.022 in	Yes

**Construction and Dimensions**

**Cabling**

Lay Length	Twists
5 in	2.4 twist/ft

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR
1.56 Ohm/1000ft

**Capacitance**

Nom. Capacitance Conductor to Conductor
---

32 pF/ft
----------

Shielding:	Unshielded
------------	------------

#### Inductance

##### Nominal Inductance

0.16 $\mu$ H/ft
-----------------

#### Current

##### Max. Recommended Current [A]

21 Amps per conductor @ 25°C A
--------------------------------

#### Voltage

##### UL Voltage Rating

300V RMS
----------

#### Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

#### Mechanical Characteristics

Bulk Cable Weight:	117 lbs/1000ft
Max Recommended Pulling Tension:	338 lbs
Min Bend Radius/Minor Axis:	3.625 in

#### Standards

NEC/(UL) Specification:	CL3
-------------------------	-----

#### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 UL Loading
UL Voltage Rating:	300 V RMS

#### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

#### Part Number

#### Variants

Item #	Color
5002UP 0101000	BLACK
5002UP 010500	BLACK
5002UP D15500	BLUE
5002UP 0081000	GRAY
5002UP 008500	GRAY
5002UP 005500	GREEN, DARK
5002UP 0091000	WHITE
5002UP 009500	WHITE

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.