



Description: Five Conductor, 6 AWG, Tray Cable
 Overall PVC Jacket

Date: 4/23/2008

JM Part Number: JM55427

Reference: TC0605/PP-0-JM

Components Five 6 AWG Insulated Conductors

Conductor: 6 AWG, 7/.0612 bare copper

Insulation: .032" nominal wall of PVC (See Color Code)

Nylon Jacket: .006" nominal wall of Clear Nylon .260"

Cable Construction

Cabling: Five conductors cabled together, FRPP fillers as necessary

Binder: Clear Mylar tape

Ripcord: Nylon ripcord under jacket

Jacket: .083" nominal wall of Black PVC .871"


Print

**E73202 5/C 6 AWG 600V TYPE TC (UL) 90C DRY 75C WET SUN RES DIR BUR
 --- LL41103 CSA AWM I/II A/B 90C 600V FT1**

Color Code

1. Black and numerically printed: 1 - ONE
2. White and numerically printed: 2 - TWO
3. Red and numerically printed: 3 - THREE
4. Blue and numerically printed: 4 - FOUR
5. Green and numerically printed: 5 - FIVE

Example:



Requirements

Temperature: 90°C
 Voltage: 600V

Approvals: UL Type TC
 CSA AWM, I/II, A/B
 Sunlight Resistant
 Direct Burial

Written By:	rjc	4/23/2008	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				