

NE8FDX-P6-B

D-shape CAT6A panel connector, shielded, feedthrough, black housing

Attention! Does not intermate with CAT6 cable connector NE8MC6-MO and NKE6S* cables.



Features & Benefits

- Ruggedized connector with CAT6A component compliance according to ISO/IEC 11801 and TIA/EIA 568-C.2
- PoE+ compliant according to 802.3at Type2
- Rugged latch lock system million fold proven
- Intermateable with the existing etherCON CAT5 range
- Shielded system - high noise immunity and EMI protection

Technical Information [hide](#)

Product

Title NE8FDX-P6-B

Gender female

Electrical

Dielectric strength 1 kVdc

Insulation resistance > 0.5 GΩ

Rated current per contact 1.5 A

Transmission performance CAT6A, acc. TIA/EIA rating
Class EA, acc. IEC/ISO/EN rating

Power over Ethernet PoE+ acc. IEEE 802.3at

Mechanical

Lifetime > 1000 mating cycles

Wiring Feedthrough

Locking device Latch lock

Mounting direction Front mounting

Material

Contact plating Au

Shell Zinc diecast (ZnAl4Cu1)

Shell plating Black

Environmental

Flammability UL 94 V-0

Temperature range -40 °C to + 70 °C

Accessories

SCDX



SCDP-*



DSS-*



SCCD-W



SCDF

