

## NF2C-B/2

Pair of professional 'Phono Plug' ('RCA'- or 'CINCH'- type) - marked red and black.

Including 2 x 2 strain reliefs for cable O.D. 3.0 mm to 7.3 mm. Additional strain relief for cable O.D. up to 8.0 mm available as accessory.



### Features & Benefits

- Makes ground before signal contact and breaks signal before ground
- No more disturbing noise and broken speaker cones
- Precisely machined to our demanding quality standards
- Neutrik unique chuck type strain relief
- Gold plated contacts
- Sleek barrel with soft touch surface and coloured shrink sleeve
- Improved ground solder lug for ease soldering

### Technical Information [hide](#)

#### Product

Title NF2C-B/2

Connection Type Profi

Gender male

#### Electrical

Capacitance between contacts  $\leq 7$  pF

Contact resistance  $>10G$  m $\Omega$

Dielectric strength 1,5 kVdc

Insulation resistance  $> 5$  G $\Omega$

Rated current per contact depends on mating connector / A

Rated voltage  $< 50$  V

#### Mechanical

Cable O.D. 3.0 - 7.3 mm

Lifetime  $> 2000$  mating cycles

Wiresize 1,5 mm<sup>2</sup>

Wiresize 16 AWG

Wiring Solder contacts

#### Material

Contact plating 5  $\mu$ m Au over 5  $\mu$ m Ni

Contacts Brass (CuZn39Pb3)

Insert PBTP 20 % GR

Shell	Brass (CuZn39Pb3)
Strain relief	Polyacetal (POM)
<b>Environmental</b>	
Flammability	UL 94 HB
Standard compliance	IEC 601-14
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

---

**Accessories**

---

CNF-9

