

NP2C

2 pole 1/4" professional phone plug, Nickel housing, Nickel contacts

Professional phone plug with robust metal shell and chuck type strain relief.



Features & Benefits

- Rugged diecast metal shell
- Chuck type strain relief for optimum cable protection
- Precision machined one-piece contacts - avoid hook up of tip contact
- Meets all prevailing standards

Technical Information [hide](#)

Product

Title NP2C

Connection Type Plug

Gender male

Electrical

Contact resistance depends on mating connector mΩ

Dielectric strength 1 kVdc

Insulation resistance > 2 GΩ (initial)

Rated current per contact depends on mating connector A

Rated voltage < 50 V

Mechanical

Cable O.D. 4 - 7 mm

Lifetime > 1000 mating cycles

Wiresize 1 mm²

Wiresize 18 AWG

Wiring Solder contacts

Material

Bushing Polyacetal (POM) + PU

Contact plating 2 μm Ni (Su)

Contacts Brass (CuZn39Pb3)

Insert Polyamide (PA 6.6 30 % GR)

Shell Zinc diecast (ZnAl4Cu1)

Shell plating Nickel

Strain relief Polyacetal (POM)

Environmental

Standard compliance	IEC 60603-11 / EIA RS-453
---------------------	---------------------------

Solderability	Complies with IEC 68-2-20
---------------	---------------------------

Temperature range	-20 °C to +65 °C
-------------------	------------------

Accessories

BSP-*



PCR-*

