



## RT4MPR

4 pole TINY xlr male chassis connector, rearmountable, nickel housing, gold plated contacts, max. panel thickness: 3 mm

- Rear mountable design
- Shielded system – high noise immunity and EMI protection
- Watertight chassis connector, even in unmated condition



### Technical Information [hide](#)

#### Product

Title	RT4MPR
-------	--------

#### Electrical

Contact resistance	< 10 mΩ
--------------------	---------

Dielectric strength	> 0.5 kVdc
---------------------	------------

Insulation resistance	> 1 GΩ
-----------------------	--------

Rated current per contact	< 5 A
---------------------------	-------

#### Mechanical

Lifetime	> 5000 mating cycles
----------	----------------------

Panel thickness	max. 3 mm
-----------------	-----------

Wiresize	0.22 mm <sup>2</sup>
----------	----------------------

Wiresize	24 AWG
----------	--------

#### Material

Contact plating	Au
-----------------	----

Contacts	Brass (CuZn38Pb3)
----------	-------------------

Insert	PA 6.6 30 % GF
--------	----------------

Shell	ZuAl4Cu1
-------	----------

Shell plating	Nickel
---------------	--------

#### Environmental

Solderability	Complies with IEC 68-2-20
---------------	---------------------------

Temperature range	-30 °C to +85 °C
-------------------	------------------

---

Data subject to change without prior notice. © 2012 NEUTRIK AG ® ALL RIGHTS RESERVED

**REAN**<sup>®</sup>  
REAN a brand of Neutrik AG