

PVC/PVC - Type SVT

Portable Cord

UL: 60°C, 300V

CSA: -60°C, 300V, FT2



IEWC Part Number	AWG	No. of Conductors	Stranding	Nominal Insulation Thickness		Nominal Jacket Thickness		Nominal O.D.		Approx. Weight		Ampacity ⁰¹
				in	mm	in	mm	in	mm	lbs/1k ft	kg/km	
SVT1802	18	2	41/34	0.015	0.4	0.030	0.8	0.235	6.0	35	52	10
SVT1803		3	41/34	0.015	0.4	0.030	0.8	0.240	6.1	40	60	10

⁰¹SVT ampacities are for general use with ambient temperature @ 30°C per NEC Table 400.5

Notes

- Soft-annealed, bare copper conductor
- Polyvinyl chloride (PVC) insulation
- Polyvinyl chloride (PVC) jacket
- RoHS Compliant
- Standard jacket colors: black, white & gray

Alternative Constructions

- Shielded constructions
- Coil cord

Available Certifications

UL: VW-1
CSA: FT1

Applications

For use in food processing, tool and appliance applications. Rated for continuous use up to 60°C.

No. of Conductors	Standard Conductor Insulation Colors
2	White, Black
3	White, Black, Green