

PVC - SPT-1, SPT-2, SPT-3

Bonded Lamp Cord
 UL: 60°C, 300V, VW-1
 CSA: 60°C, 300V, FT1



| IEWC Part Number | AWG | No. of Conductors | Stranding | Nominal Insulation Thickness | | Nominal O.D. | | Approx. Weight | | UL Type |
|------------------|-----|-------------------|-----------|------------------------------|-----|---------------|-------------|----------------|-------|---------|
| | | | | in | mm | in | mm | lbs/1k ft | kg/km | |
| SPT1802 | 18 | 2 | 41/34 | 0.030 | 0.8 | 0.110 x 0.215 | 2.8 x 5.5 | 17 | 25 | SPT-1 |
| | | | 41/34 | 0.045 | 1.1 | 0.140 x 0.265 | 3.6 x 6.7 | 14 | 21 | SPT-2 |
| | | | 41/34 | 0.060 | 1.5 | 0.170 x 0.330 | 4.3 x 8.4 | 33 | 49 | SPT-3 |
| SPT1803 | | 3 | 41/34 | 0.030 | 0.8 | 0.110 x 0.275 | 2.8 x 7.0 | 25 | 37 | SPT-1 |
| | | | 41/34 | 0.045 | 1.1 | 0.140 x 0.360 | 3.6 x 9.1 | 33 | 49 | SPT-2 |
| | | | 41/34 | 0.060 | 1.5 | 0.170 x 0.375 | 4.3 x 9.5 | 46 | 68 | SPT-3 |
| SPT1602 | 16 | 2 | 65/34 | 0.045 | 1.1 | 0.155 x 0.285 | 3.9 x 7.2 | 34 | 51 | SPT-2 |
| | | | 65/34 | 0.060 | 1.5 | 0.180 x 0.345 | 4.6 x 8.8 | 42 | 62 | SPT-3 |
| SPT1603 | | 3 | 65/34 | 0.045 | 1.1 | 0.155 x 0.380 | 3.9 x 9.7 | 57 | 85 | SPT-2 |
| | | | 65/34 | 0.060 | 1.5 | 0.180 x 0.415 | 4.6 x 10.5 | 57 | 85 | SPT-3 |
| SPT1402 | 14 | 2 | 41/30 | 0.080 | 2.0 | 0.235 x 0.420 | 6.0 x 10.7 | 66 | 98 | SPT-3 |
| SPT1403 | | 3 | 41/30 | 0.080 | 2.0 | 0.235 x 0.505 | 6.0 x 12.8 | 92 | 137 | SPT-3 |
| SPT1202 | 12 | 2 | 65/30 | 0.095 | 2.4 | 0.285 x 0.490 | 7.2 x 12.5 | 96 | 143 | SPT-3 |
| SPT1203 | | 3 | 65/30 | 0.095 | 2.4 | 0.285 x 0.585 | 7.2 x 14.9 | 124 | 185 | SPT-3 |
| SPT1003 | 10 | 3 | 105/30 | 0.110 | 2.8 | 0.445 x 0.700 | 11.3 x 17.8 | 237 | 353 | SPT-3 |

Notes

- Soft-annealed, bare copper conductor
- Polyvinyl chloride (PVC) insulation
- RoHS Compliant
- Standard insulation colors: black, brown, clear & white

Alternative Constructions

- 3 conductor with green ground
- Temperature range up to 105°C

Available Certifications

CSA: FT2

Applications

For use in heating & cooling, lighting and appliance applications. Rated for continuous use up to 60°C.