


PVC/Nylon/PVC - Pendant Cable

Hoist and Control Station Cable With Twin External Insulated Steel Messengers
-10°C to 90°C, 600V



IEWC Part Number	AWG	No. of Conductors	Stranding	Nominal Insulation Thickness		Nominal Jacket Thickness		Nominal O.D.		Approx. Weight	
				in	mm	in	mm	in	mm	lbs/1k ft	kg/km
RPC1608*S	16	8	65/34	0.019	0.5	0.047	1.2	0.465	11.8	196	292
RPC1612*S		12	65/34	0.019	0.5	0.063	1.6	0.550	14.0	248	369
RPC1616*S		16	65/34	0.019	0.5	0.063	1.6	0.605	15.4	302	449
RPC1624*S		24	65/34	0.019	0.5	0.063	1.6	0.745	18.9	430	640

Notes

- Soft-annealed, bare copper conductor
- Polyvinyl chloride (PVC) insulation
- Nylon sheath over insulation
- Polyvinyl chloride (PVC) jacket
- Twin insulated 1/16" 7x7 galvanized steel messengers
- Standard jacket color: yellow
- Conductor color code per ICEA Method 1, Table E-1 on 215 with green ground conductor

Applications

For use in hoist and pendant applications. Rated for continuous use from -10°C up to 90°C.