


PVC/Nylon/PVC - MTW Pendant Cable

Hoist and Control Station Cable

UL: -10°C to 90°C, 600V

CSA: -10°C to 90°C, 600V, AWM I A, FT1



IEWC Part Number	AWG	No. of Conductors	Stranding	Nominal Insulation Thickness		Nominal Jacket Thickness		Nominal O.D.		Approx. Weight	
				in	mm	in	mm	in	mm	lbs/1k ft	kg/km
RPC1608	16	8	65/34	0.020	0.5	0.047	1.2	0.465	11.8	145	216
RPC1612		12	65/34	0.020	0.5	0.063	1.6	0.550	14.0	200	298
RPC1616		16	65/34	0.020	0.5	0.063	1.6	0.605	15.4	255	379
RPC1624		24	65/34	0.020	0.5	0.063	1.6	0.745	18.9	375	558
RPC1630		30	65/34	0.020	0.5	0.063	1.6	0.785	19.9	445	662
RPC1636		36	65/34	0.020	0.5	0.085	2.2	0.885	22.5	540	804

Notes

- Soft-annealed, bare copper conductor
- Polyvinyl chloride (PVC) insulation
- Nylon sheath over insulation
- Polyvinyl chloride (PVC) jacket
- Standard jacket color: yellow
- Conductor color code per ICEA Method 1, Table E-1 on 215 with green ground conductor

Applications

For use in festooning, hoist and pendant applications. Rated for continuous use from -10°C up to 90°C.