

# EPDM - Type 3311 (CL905)

Motor Lead and Internal Appliance Wire

UL: -40°C to 90°C, 600V

CSA: -40°C to 90°C, 600V



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
<b>3311/08</b>	8	133/29	0.080	2.0	0.351	8.9	90	134
<b>3311/06</b>	6	259/30	0.080	2.0	0.380	9.7	139	207
<b>3311/04</b>	4	420/30	0.080	2.0	0.424	10.8	189	281
<b>3311/02</b>	2	665/30	0.080	2.0	0.485	12.3	290	432
<b>3311/01</b>	1	840/30	0.095	2.4	0.563	14.3	350	521
<b>3311/1/0</b>	1/0	1064/30	0.095	2.4	0.625	15.9	460	685
<b>3311/2/0</b>	2/0	1330/30	0.095	2.4	0.650	16.5	536	798
<b>3311/3/0</b>	3/0	1672/30	0.095	2.4	0.746	18.9	663	987
<b>3311/4/0</b>	4/0	2109/30	0.095	2.4	0.800	20.3	820	1220

### Notes

- Soft-annealed, bare copper conductor
- Ethylene propylene diene monomer (EPDM) insulation
- Standard insulation colors: black and red

### Alternative Constructions

- Soft-annealed, tinned copper conductor

### Applications

For use in electric motor & generator, heating & cooling and appliance applications. Rated for continuous use from -40°C up to 90°C.