

Tight Buffer Distribution Riser Cable

Type OFNR, CSA FT4, Indoor*



| CATALOG NUMBER | FIBER COUNT | NO. OF SUB-UNITS | NOMINAL CABLE DIAMETER | | NOMINAL CABLE WEIGHT | | MAXIMUM TENSILE LOAD | | | |
|----------------|-------------|------------------|------------------------|----|----------------------|-------|----------------------|------|------------|-----|
| | | | IN | mm | LBS/1000' | kg/km | INSTALLATION | | IN-SERVICE | |
| | | | | | | | LBS | N | LBS | N |
| XX0021PNR | 2 | — | 0.19 | 5 | 14 | 20 | 225 | 1000 | 65 | 290 |
| XX0061PNR | 6 | — | 0.20 | 5 | 18 | 27 | 225 | 1000 | 65 | 290 |
| XX0121PNR | 12 | — | 0.25 | 6 | 24 | 36 | 320 | 1425 | 112 | 500 |
| XX0241P1R | 24 | 4 | 0.34 | 9 | 47 | 70 | 330 | 1425 | 112 | 500 |

XX denotes glass type.

NOTE: More fiber counts are available upon request. See Fiber Optic Catalog for complete product information.

*Not for aerial or direct burial applications.

Tight Buffer Distribution Plenum Cable

Type OFNP, CSA FT6, Indoor*



| CATALOG NUMBER | FIBER COUNT | NO. OF SUB-UNITS | NOMINAL CABLE DIAMETER | | NOMINAL CABLE WEIGHT | | MAXIMUM TENSILE LOAD | | | |
|----------------|-------------|------------------|------------------------|----|----------------------|-------|----------------------|------|------------|-----|
| | | | IN | mm | LBS/1000' | kg/km | INSTALLATION | | IN-SERVICE | |
| | | | | | | | LBS | N | LBS | N |
| XX0021PNU | 2 | — | 0.17 | 4 | 12 | 17 | 225 | 1000 | 65 | 290 |
| XX0061PNU | 6 | — | 0.18 | 5 | 16 | 24 | 225 | 1000 | 65 | 290 |
| XX0121PNU | 12 | — | 0.22 | 6 | 23 | 34 | 320 | 1423 | 112 | 500 |
| XX0241PNU | 24 | — | 0.32 | 8 | 45 | 67 | 320 | 1423 | 112 | 500 |

XX denotes glass type.

NOTE: More fiber counts are available upon request. See Fiber Optic Catalog for complete product information.

*Not for aerial or direct burial applications.